



EU Power Cable C13 to CEE 7/7, 5 m

AC Power Cord with C13 to European Mains 2-pin, 10 A, 250 V, For PC, Monitor, Printer and TV, Black

Part No.: **308700**

EAN-13: 0766623308700 | UPC: 766623308700

PC Power Cord or Monitor Power Cable 5m - Great as a replacement or spare AC power supply cable for printer, TV, server, and more

The Manhattan EU Power Cable CEE 7/7 to C13, 5 m easily connects and extends the reach between a power outlet and a personal computer, monitor, printer, power adapter or other compatible piece of equipment. Ideal for new systems or replacement applications, this power cable is engineered and built from quality materials that meet current safety approvals to deliver and maintain reliable connections. Fully molded boots with strain relief, a durable PVC jacket, and heavy-duty construction enable this power cable to help provide maximum electrical conductivity to transmit dependable power where and when needed.

Features:

- Connects a device with three-pin C14 inlet to a standard two-slot EU AC or similar power outlet
- Great for powering a PC, monitor, printer, TV, scanner, server and more
- Ideal replacement, upgrade or spare power cable for misplaced or overused ones

- Universal CEE 7/7 hybrid plug fits both European type F and French type E sockets
- Pure bare copper wire for maximum conductivity
- Flexible, durable PVC jacket with heavy-duty strain relief
- High-temperature resistance for use in areas that are not air conditioned
- For indoor use only
- Lifetime warranty

Specifications:

Standards and Certifications

- CE
- RoHS
- REACH
- IEC 60320
- VDE
- UKCA

General

- One CEE 7/7 male
- One IEC 60320 C13 female
- Maximum current: 10.0 A
- Maximum voltage: 250.0 V AC

Physical

- Wire: 100% pure bare copper (Cu)
- Jacket and boot material: PVC
- Number of cores: 3
- Number of strands / strand thickness: 32 / 0.2 mm
- Insulation thickness: 0.6 mm
- Jacket thickness: 0.8 mm
- Nominal overall diameter: 6.8 mm
- Length: 5 m
- Cable type: H05VV-F 3G 1.0 mm²
- Net weight: 340 g
- Gross weight: 350 g

Environmental

- Operation temperature: -10 - 60°C
- Operating humidity (non-condensing): 10 - 85%
- Storage temperature: -20 - 70°C
- Storage humidity (non-condensing): 5 - 90%

Package Contents

- EU Power Cord CEE 7/7 to C13, 5m

