


245523 2-Port 30W GaN Slim USB PD Charger, USB-C x1, USB-A x1

Product Images





Short Description

- USB Power Delivery (PD) 3.0 technology with quick charge function.
- GaN Technology: Gallium Nitride for higher efficiency and compact size.
- Input voltage: 100-240V AC, 50/60Hz, 0.8A
- USB-C output: DC 5V==3A, 9V==3A, 12V==2.5A, 15V==2A, 20V==1.5A(Max. 30W)
- PPS: 3.3-11V==3A , 3.3-16V==2A
- USB-A Output: DC 5V==3A, 9V==2A, 12V==1.5A (Max. 18W)
- USB A+C Output: DC 5V==3A Shared (Max. 15W)
- Compatible with most of smartphones and tablets with USB-C charging
- Slim & Lightweight Design: Ultra-compact form factor for portability and travel
- Overload, overvoltage, overcurrent and short-circuit protection
- Dual-Port Output: 1x USB-C + 1x USB-A for simultaneous charging of two devices

Description

The Equip 245523 2-Port 30W GaN Slim USB PD Charger is a high-performance, compact power solution designed for modern digital lifestyles. Powered by advanced GaN (Gallium Nitride) technology, it achieves superior energy efficiency and reduced heat generation compared to conventional silicon chargers. This allows for a slimmer and lighter design, making it easy to carry in a pocket, purse, or laptop bag—perfect for home, office, and travel use.

Featuring one USB-C Power Delivery (PD) port and one USB-A port, the charger provides flexible charging options for multiple devices. The USB-C PD port delivers up to 30W of fast charging power, making it ideal for smartphones, tablets, handheld game consoles, and even smaller laptops or ultrabooks. The USB-A port supports standard charging for accessories such as wireless earbuds, Bluetooth speakers, or legacy devices, ensuring broad compatibility.

Additional Information

Number of outputs.	2
USB Type-A ports quantity.	1
Fast charging technology.	Quick Charge 3.0
USB Type-C ports quantity.	1
Programmable power supply (PPS) (YES/NO).	No
Port 1 Power Output.	USB-C Output: DC 5V===3A, 9V===3A, 12V===2.5A; 15V===2A, 20V===1.5A (Max.30W)
Port 2 Power Output.	USB-A Output: DC 5V===3A, 9V===2A, 12V===1.5A (Max. 18W)
Port 3 Power Output.	USB A+C Output: DC 5V===3A Shared (Max. 15W)
Sustainability Compliance.	No
Power input.	100-240V AC, 50/60Hz, 0.8A
Approval and Compliance.	CE ,ROHS
Package Contents.	2-Port 30W GaN Slim USB PD Charger
Color.	White
EAN.	4015867242698
Model Number.	245523
Dimensions (W x D x H).	15 x 36 x 81 mm
Product weight (kg).	0.053

