

Key Features

- ❑ Processor Intel Celeron J6412 provide competitive performance
- ❑ All aluminium alloy shell, Fanless design for silent operation
- ❑ Dual HDMI Port, support duplicate or extend mode
- ❑ Various interfaces meet the needs of different scenarios



MODEL		HK600
Processor		Intel Celeron J6412, Elkhart Lake, Quad-core 2.0GHz up to 2.6GHz
Operating System		Windows 10 / Windows11 / Linux
Memory		1*SO-DIMM DDR4 3200MHz 4GB, up to 16GB
Storage		M.2 2280 SATA 128GB, up to 512GB
Power Supply		24V 120W (Standard, support for use all Power USB Ports) 24V 90W (Optional, support for use no more than 1 Power USB)
I/O Ports	Serial Port	3*DB9 COM Ports
		1*RJ50 COM Ports
		COM3/COM4 can be set voltage
	USB	2*USB 3.0 TYPE A
		2*USB 2.0 TYPE A
		3*12V PowerUSB
		1*24V PowerUSB
	LAN	1*RJ45, supports 10/100/1000Mbps adaptive network
	Cash Drawer	1*RJ11 24V cash drawer Port
	Audio	1*Line-MIC
	Power-in	1*24V Power-in
	Video	2*HDMI Ports
	Button	1*Power Button
Optional features	Wireless	Wi-Fi & BT feature
	Bracket	Rail Bracket on both side (for Wall mount / Desk mount)
	Cable	Power Cable for Monitors (connect to 12V PowerUSB)
Dimensions (LxWxH)		224×156×70mm (without antenna)
Weight		1.95Kg
Operating Voltage		100V~240V
Casing Material		High-quality aluminum alloy / Sandblasted oxidation
Environment	Operating	-10°C - 60°C/5%-95% RH non-condensing
	Storage	-20°C - 85°C/5%-95% RH non-condensing
EMC and Safety		CE / FCC
Colour		Silver-Gray



□ Variety I/O Ports



Disclaimer: All products specifications are subject to change without notice.

QINGDAO HISTONE INTELLIGENT COMMERCIAL SYSTEM CO.,LTD.
Wisdom Valley, NO.8 Shengshui Road, Laoshan District, Qingdao City, China.

Tel: +86 (532) 66069168

✉ infopos@histonetec.com

🌐 www.hics.histonetec.com

HiStone