

# LANCOM Direct Attach Cable

Optimal interconnections between your LANCOM devices!



The LANCOM Direct Attach Cables enable fast and uncomplicated interconnections between LANCOM switches, gateways, and firewalls - a practical alternative to using individual SFP transceivers. Time and cost input are optimally balanced. All Direct Attach Cables are tested for compatibility with LANCOM products and guarantee highly reliable and fast connections.

- [LANCOM SFP-DAC10-1M /-3M](#)
- [LANCOM SFP-DAC25-1M /-3M](#)
- [LANCOM SFP-DAC40-1M /-3M](#)
- [LANCOM SFP-DD-DAC50-1M /-2.5M](#)
- [LANCOM SFP-DAC100-1M /-3M](#)

**All transceivers are Class 1 Laser products in accordance with FDA/CDRH and IEC-60825 standards. These devices are designed to be eye safety compliant under the specified operating conditions. It is essential to ensure that they are always operated within these conditions to maintain their safety and compliance.**

# LANCOM Direct Attach Cable

## **LANCOM SFP-DAC10-1M / SFP-DAC10-3M**

Direct attach cable for 10 Gbps networking of LANCOM devices



- Direct attach copper cable for usage in SFP+ ports
- Up to 10 Gbps link speed (1G / 10G)
- Full-duplex mode
- Operating temperature 0–70 °C
- 1 m / 3 m cable length
- Swappable during system operation



# LANCOM Direct Attach Cable

## **LANCOM SFP-DAC25-1M / SFP-DAC25-3M**

Direct attach cable for 25 Gbps networking of LANCOM devices



- Direct attach copper cable for usage in SFP28 ports
- Up to 25 Gbps link speed
- Full-duplex mode
- Operating temperature 0–70 °C
- 1 m / 3 m cable length
- Swappable during system operation

# LANCOM Direct Attach Cable

## **LANCOM SFP-DAC40-1M / SFP-DAC40-3M**

Direct attach cable for 40 Gbps networking of LANCOM devices



- Direct attach copper cable for usage in QSFP+ ports
- Up to 40 Gbps link speed
- Full duplex operation
- Operating temperature 0–70 °C
- 1 m / 3 m cable length
- Swappable during system operation

# LANCOM Direct Attach Cable

## **LANCOM SFP-DD-DAC50-1M / SFP-DD-DAC50-2.5M**

Direct attach cable for 50 Gbps networking of LANCOM devices



- Stacking cable for creating a stack with LANCOM XS-6128QF
- Direct attach copper cable for usage in SFP-DD ports
- Up to 50 Gbps link speed
- Full duplex operation
- Operating temperature 0–70 °C
- 1 m / 2.5 m cable length
- Swappable during system operation

# LANCOM Direct Attach Cable

## **LANCOM SFP-DAC100-1M / SFP-DAC100-3M**

100 Gbps Direct Attach Cable (DAC) for direct connection of LANCOM devices



- Up to 100 Gbps link speed
- Full duplex operation
- Operating temperature 0–70 °C
- Cable length 1 m / 3 m
- Swappable during system operation
- Also available as 8-piece bulk package



# LANCOM Direct Attach Cable

|             | <b>LANCOM<br/>SFP-DAC10-1M<br/>SFP-DAC10-3M</b> | <b>LANCOM<br/>SFP-DAC25-1M<br/>SFP-DAC25-3M</b> | <b>LANCOM<br/>SFP-DAC40-1M<br/>SFP-DAC40-3M</b> | <b>LANCOM<br/>SFP-DD-DAC50-1M<br/>SFP-DD-DAC50-2.5M</b> |
|-------------|-------------------------------------------------|-------------------------------------------------|-------------------------------------------------|---------------------------------------------------------|
| Item number | SFP-DAC10-1M<br>61495<br>60194 (Bulk 8)         | SFP-DAC25-1M<br>60180<br>60195 (Bulk 8)         | SFP-DAC40-1M<br>60176<br>60196 (Bulk 8)         | SFP-DD-DAC50-1M<br>60179<br>60197 (Bulk 8)              |
|             | SFP-DAC10-3M<br>60175                           | SFP-DAC25-3M<br>60181                           | SFP-DAC40-3M<br>60177                           | SFP-DD-DAC50-2.5M<br>60178                              |
| Warranty    | 2 years                                         | 2 years                                         | 2 years                                         | 2 years                                                 |

  

|             | <b>LANCOM<br/>SFP-DAC100-1M<br/>SFP-DAC100-3M</b> |
|-------------|---------------------------------------------------|
| Item number | SFP-DAC100-1M<br>60203                            |
|             | SFP-DAC100-3M<br>60204                            |
| Warranty    | 2 years                                           |

**Note** To use the LANCOM Direct Attach Cables in a LANCOM switch, at least LCOS SX 3.30 RU3 is required.

LANCOM devices and other LANCOM accessories compatible to the LANCOM Direct Attach Cables can be found under [www.lancom-systems.com/products/software-accessories/accessories/lancom-direct-attach-cable#devices](http://www.lancom-systems.com/products/software-accessories/accessories/lancom-direct-attach-cable#devices)