





PIN OUT

P1		P2	
1		1	WHITE/ORANGE
2		2	ORANGE
3		3	WHITE/GREEN
6		6	GREEN
4		4	BLUE
5		5	WHITE/BLUE
7		7	WHITE/BROWN
8		8	BROWN

A-A
10:1



NOTE:


Electrical test!

100% open short & miss wire test.
Pass Fluke test (Random test).

RoHS 2.0 Compliant, REACH Compliant.

MATERIAL LIST

⑦	PACKAGE	TECHLY PROFESSIONAL PE ZIP BAG+BARCODE LABEL	1
⑥	PRINTING	WWW.TECHLY.COM CATEGORY 6A U/FTP CU TPE SLIM PATCH CABLE 4PR STRANDED 32AWG CE ROHS	
⑤	CABLE	CAT.6A U/FTP SLIM CABLE, (7/0.08BC*1P+AM)*4P+7/0.08BC+TPE, OD: 3.6±0.2MM	L
④	MOLD BOOT	ROTATABLE PART, MATERIAL: PVC	1
③	MOLD BOOT	ROTATABLE PART, MATERIAL: PVC,	1
②	CONNECTOR	CAT.6A RJ45 SHORT PLUG, SHIELD, 3U', COLOR: TRANSPARENT BLUE	1
①	CONNECTOR	CAT.6A RJ45 SHORT PLUG, SHIELD, 3U', COLOR: TRANSPARENT BLUE	1
No.	PART NAME	DESCRIPTION	QTY



LENGTH LIST

MODEL	LENGTH
ICOC UF6A-TPE36-005B	500±20mm
ICOC UF6A-TPE36-010B	1000±20mm
ICOC UF6A-TPE36-020B	2000±20mm
ICOC UF6A-TPE36-030B	3000±30mm
ICOC UF6A-TPE36-050B	5000±50mm