

## Optical smoke- & heat alarm, linkable, white

**NORDIC**  
QUALITY



- Radio link
- Heat detection
- Heat sensitivity: 54-70°C
- Loud 85dB(A) alarm signal
- Wireless frequency 433 MHz
- Connect up to 30 detectors
- Button for monthly testing
- Silence function & Low battery alarm
- Smoke sensitivity: 0.100-0.163 dB/m
- Safety clip feature, prevents mounting of smoke alarm without battery installed

**Protect your indoor spaces with this optical smoke & heat alarm. Designed to provide early warnings, it detects smoke with sensitivity from 0.100-0.163 dB/m and heat between 54-70°C. The loud 85dB(A) alarm ensures alerts are heard clearly. It operates on a 433 MHz frequency, and can interconnect up to 30 units, making it ideal for schools & offices. Features include a**

Package contents: Optical smoke alarm

## SPECIFICATIONS

---

### LOGISTIC

---

|                          |               |
|--------------------------|---------------|
| Item number              | 189911        |
| Manufacturer part number | GS558A        |
| Country of origin        | China         |
| Sales unit bar code      | 5706470097674 |
| Sales unit height        | 135 mm        |
| Sales unit width         | 135 mm        |
| Sales unit depth         | 55 mm         |
| Sales unit gross weight  | 0.19 kg       |
| Sales unit net weight    | 0.17 kg       |
| Inner carton height      | 0 mm          |
| Inner carton width       | 0 mm          |
| Inner carton depth       | 0 mm          |
| Inner carton weight      | 0 kg          |
| Inner carton quantity    | 10            |
| Master carton height     | 315 mm        |
| Master carton width      | 550 mm        |
| Master carton depth      | 290 mm        |
| Master carton weight     | 10 kg         |
| Master carton quantity   | 40            |