

DisplayPort 1.2 Cable, 4K 60Hz



Description

Shielding: foil + braiding

Conductor: bare copper, Jacket: PVC

Plugs and contacts gold plated

Pin 20: DP_PWR not connected

Housing 360° shielded, moulded with locking protection

DisplayPort v1.2 compliant

Supports resolutions up to 4096 x 2160 Pixel (4k2k)

Supports HDCP 1.3 and DPCP

General data

Type of connector connection 1	DisplayPort
Number of poles connection 1	20
Connection type connection 1	Plug
Type of connector connection 2	DisplayPort
Number of poles connection 2	20
Connection type connection 2	Plug

Available variants

Article no.	Title	Length	Colour
K5560SW.0,5	DisplayPort 1.2 Cable, 4K60Hz, M-M, 0,5m, black	0.5 m	black
Article no.	Title	Length	Colour
K5560SW.1	DisplayPort 1.2 Anschlusskabel, 4K60HZ,Stecker-Stecker, 1m, schwarz	1.0 m	black
Article no.	Title	Length	Colour
K5560SW.2	DisplayPort 1.2 Cable, 4K60HZ, Plug-Plug, 2m, black	2.0 m	black
K5560SW.5	DisplayPort 1.2 Cable, 4K60Hz, M-M, 5m, black	5.0 m	black
K5560SW.3	DisplayPort 1.2 Cable, 4K60Hz, M-M, 3m, black	3.0 m	black
K5560SW.10	DisplayPort 1.2 Cable, 4K60Hz, M-M, 10m, black	10.0 m	black

This datasheet was created automatically on 25-07-2022 . Technical changes reserved.

