

# 19-inch wall-mounted housing Basic Plus

**roline**<sup>®</sup>  
Designed for Professionals

## Data sheet



**The ROLINE Basic Plus series wall-mounted enclosures have been specially designed for flexible network cabling. This series represents an ideal balance between the ROLINE PRO and ROLINE Basic series.**

### Characteristics:

- Load capacity: 80 kg
- Front door made of tempered glass, lockable
- Side panels are fitted with a quick-release mechanism and are removable
- Roof with cut-out for fan modules
- Cable feed possible on roof and base
- Ventilation slots for passive ventilation and air extraction
- incl. mounting material
- Color: Light grey, RAL 7035 or Jet black, RAL 9005
- IP protection class: IP20
- Delivery: assembled

# 19-inch wall-mounted housing Basic Plus



## Data sheet

The ROLINE Basic Plus series offers a versatile selection of wall-mounted enclosures in various height units from 4 U to 18 U and in the colours grey (RAL 7035) and black (RAL 9005).

| Manuf. no. | Height | Width (mm) | Depth (mm) | Colour / RAL     |
|------------|--------|------------|------------|------------------|
| 26.21.0122 | 4 U    | 600        | 450        | grey / RAL 7035  |
| 26.21.0282 | 4 U    | 600        | 450        | black / RAL 9005 |
| 26.21.0128 | 4 U    | 600        | 600        | grey / RAL 7035  |
| 26.21.0288 | 4 U    | 600        | 600        | black / RAL 9005 |
| 26.21.0123 | 6 U    | 600        | 450        | grey / RAL 7035  |
| 26.21.0283 | 6 U    | 600        | 450        | black / RAL 9005 |
| 26.21.0129 | 6 U    | 600        | 600        | grey / RAL 7035  |
| 26.21.0289 | 6 U    | 600        | 600        | black / RAL 9005 |
| 26.21.0124 | 9 U    | 600        | 450        | grey / RAL 7035  |
| 26.21.0284 | 9 U    | 600        | 450        | black / RAL 9005 |
| 26.21.0130 | 9 U    | 600        | 600        | grey / RAL 7035  |
| 26.21.0290 | 9 U    | 600        | 600        | black / RAL 9005 |
| 26.21.0125 | 12 U   | 600        | 450        | grey / RAL 7035  |
| 26.21.0285 | 12 U   | 600        | 450        | black / RAL 9005 |
| 26.21.0131 | 12 U   | 600        | 600        | grey / RAL 7035  |
| 26.21.0291 | 12 U   | 600        | 600        | black / RAL 9005 |
| 26.21.0126 | 15 U   | 600        | 450        | grey / RAL 7035  |
| 26.21.0286 | 15 U   | 600        | 450        | black / RAL 9005 |
| 26.21.0132 | 15 U   | 600        | 600        | grey / RAL 7035  |
| 26.21.0292 | 15 U   | 600        | 600        | black / RAL 9005 |
| 26.21.0127 | 18 U   | 600        | 450        | grey / RAL 7035  |
| 26.21.0287 | 18 U   | 600        | 450        | black / RAL 9005 |
| 26.21.0133 | 18 U   | 600        | 600        | grey / RAL 7035  |
| 26.21.0293 | 18 U   | 600        | 600        | black / RAL 9005 |

# 19-inch wall-mounted housing Basic Plus

**roline**<sup>®</sup>  
Designed for Professionals

## Data sheet



Tempered glass front door



Rear panel with cut-outs



Removable side panels (quick-release mechanism)



Integrated locking cylinder



Base plate with cut-out



Roof with cut-outs for ventilation