



STORM 80c Feature Sheet

Main Features

- **80W Full-Color Compact Point Source Fixture**
- **New Breakthrough Proprietary LED Chipset:** Blue, Lime, Amber, Indigo, Red, Cyan, Green (BLAIR-CG)
- **19,850 Lux @1m (5600K)** When Using Included 35° Hyper Reflector
- **CCT Range of 1,800K-20,000K**
- **Advanced Diode Color Mixing** Allows Fixture to More Effectively Utilize Each Diode's Light Output
- **Advanced White Point Control** with **Green/Magenta Color Correction** ($\pm$ G 100% Full ASC MITC Range)
- **Ultra-High Color Accuracy:** CRI $\geq$ 97, TLCI $\geq$ 98, CQS [CIE D5600] $\geq$ 96, SSI [P3200]: 88, SSI [CIE D5600]: 84, TM-30 Rf (avg) 96, TM-30 Rg (avg) 103
- **90%+ Coverage** of Rec.2020 color gamut
- **Compact Design** (Lamp Head Weight with Yoke: 1.35kg / 2.98lbs)
- **Removable Yoke** Offers **360° Rotation** of Lamp Head
- **Versatile Rigging Potential** with Four 3/8-16in Threads
- **All-New Robust Mini ProLock Locking Accessory Mount Design** Allows For More Secure and Optically Aligned Modifier Accessory Connection
- **IP65 Weather Resistance**
- **Multiple Control Methods:** Sidus Link and Sidus Link Pro App, LumenRadio CRMX, 16-bit 5-Pin DMX512 In & Out
- **Smooth 0.1-100% Stepless Dimming**
- **Minimum Output:** <19.8 lux @ 1m, 5,600K
- **Dual Output Modes:** Max and Constant
- **High-Speed Photography, Lead-Follow, and Studio Modes**
- **4 Fan Modes:** Smart, High, Medium, Silent
- **74 DMX Control Profiles** with **Multiple DMX Dimming Modes** and **Customizable DMX Signal Loss Behaviors**
- **4 Dimming Curves:** Linear, Exponential, Logarithmic, S-shaped
- **15 Built-In Light Effects:** Lightning II; Paparazzi; Color Chase; Candle; Explosion II; Strobe II; Cop Car II; Fireworks; Welding II; Pulsing II; Faulty Bulb II; Fire II; Club lights; TV II; Party Lights
- **10 Savable Presets**



Sales & Shipping Information

Product Name	STORM 80c	
	SKU	UPC
US Plug	AP00336A20	6977162451107
EU Plug	AP00336A21	6977162451114
AU Plug	AP00336A22	6977162451121
UK Plug	AP00336A23	6977162451138
JP Plug	AP00336A24	6977162451145
CN Plug	AP07050020	6977162451152
Packing Dimensions	40.5 × 23.6 × 25.5cm / 16.0 × 9.3 × 10.0in	
Net Weight	2.30kg / 5.07lbs	
Gross Weight	4.20kg / 9.26lbs	
Carton Quantity	2 pcs	
Carton Dimensions	49.0 × 42.0 × 27.5cm / 19.3 × 16.5 × 10.8in	
Carton Weight	9.45kg / 20.83lbs	



Product Description

Introducing the Aputure STORM 80c, Aputure's second light in our new STORM family and first to feature our new BLAIR-CG LED chipset. As an 80W color-tunable point source fixture with a color engine based on our breakthrough BLAIR chipset, a Mini ProLock locking Bowens mount, and compact profile, the STORM 80c is a feature-packed versatile fixture suitable for a tremendous range of professional imaging applications from high-end film productions to small-crew video or photo shoots.

With the new BLAIR-CG chipset, the STORM 80c delivers exceptional brightness and color accuracy. The added Cyan and Green diodes allows the STORM 80c to cover 90%+ of the Rec.2020 color gamut, giving users access to a far greater range of saturated colors compared to the BLAIR chipset. The STORM 80c offers 19,850 lux @1m at 5,600K with its included hyper reflector while maintaining an SSI [P3200] of 88 and SSI [CIE D5600] of 84 at 3,200K and 5,600K respectively. The inclusion of an indigo diode in this chipset enhances the colors of fluorescing materials, resulting in an image that is lit more accurately to match natural daylight and tungsten sources.

Featuring a wide CCT range of 1,800K-20,000K and advanced white-point control with green-magenta color correction ($\pm$ G 100% ASC MITC range), this fixture offers the versatility and critical color accuracy that professionals call for on set.

Equipped with advanced dimming technology, the STORM 80c ensures flicker-free, color-accurate operation during shooting even at its lowest output level of <19.8lux @1m (5,600K). In addition, this dimming technology provides users with an unprecedented 0.1-100% stepless brightness control.

Armed with a newly designed Mini ProLock locking accessory mount, the STORM 80c can support compact modifiers designed specifically for the 80c or be adapted to a full-size Bowens mount while maintaining an easy coupling procedure that reduces the need to make rotational adjustments with accessories to achieve a secure, optically aligned lock.

Featuring comprehensive lighting control protocol options, including 16-bit DMX512, LumenRadio CRMX, and Sidus Link/Sidus Link Pro® App control, the STORM 80c ensures seamless integration into professional lighting workflows at the lamp head and behind the console.

The STORM 80c ships with the new OSII operating system installed, which gives users a more seamless, quick, and intuitive user experience when operating the fixture.

With a rugged IP65 dust and weather resistant rating, the STORM 80c is capable of withstanding even the most demanding filming environments in inclement weather without any impact to performance or reliability.

Target Audience

The STORM 80c is a cutting-edge lighting fixture designed to cater to a diverse range of professionals within the film and photography industries calling for compact, color tunable, and versatile lights, including cinematographers, lighting technicians, videographers, and photographers.

For cinematographers, this advanced LED fixture offers a nifty lighting solution deployable in any shooting condition. Armed with the new BLAIR-CG light engine and IP65 weather resistance, the STORM 80c can be used to give color tunable and accurate hair and fill lights for subjects in any filming condition, rain or shine.

Lighting technicians will appreciate the STORM 80c's ease of integration into professional setups. Equipped with a variety of control options, including 16-bit DMX512, LumenRadio CRMX, and Sidus Link® App control, this fixture seamlessly adapts to complex lighting networks, enhancing workflow efficiency, and carries a small footprint on set.

Videographers benefit from the STORM 80c's output to size ratio, providing 20,185 lux at 5600K at 1 meter while weighing just under 3 pounds. With its versatile Mini ProLock Mount, videographers have the flexibility to quickly achieve their desired lighting looks with modifiers designed and optimized for the STORM 80c.

Photographers requiring a portable professional-grade lighting solution will find the STORM 80c to be an indispensable tool in their arsenal. With its small form factor and full color tunability, the STORM 80c can be used across a wide range of photographic applications, from studio portraits to outdoor shoots.

Whether you're a seasoned cinematographer, lighting technician, videographer, or photographer, the STORM 80c empowers you to elevate your craft with its high color accuracy, versatility, and reliability, ensuring exceptional results in every production or photo shoot.



STORM 80c Photometrics

CCT	Dis.	Bare COB	Hyper Reflector	Mini Lantern Diffuser
1,800K	1m	4,827 lux 430 fc	13,915 lux 1,236 fc	875 lux 79 fc
	3m	524 lux 49 fc	1,391 lux 129 fc	98 lux 9 fc
3,200K	1m	6,607 lux 614 fc	19,443 lux 1,807 fc	1,203 lux 112 fc
	3m	729 lux 68 fc	1,942 lux 181 fc	137 lux 13 fc
4,300K	1m	6,722 lux 625 fc	19,432 lux 1,806 fc	1,198 lux 111 fc
	3m	728 lux 68 fc	1,941 lux 180 fc	136 lux 13 fc
5,600K	1m	6,502 lux 604 fc	19,850 lux 1,845 fc	1,183 lux 110 fc
	3m	721 lux 67 fc	1,924 lux 179 fc	135 lux 13 fc
6,500K	1m	6,554 lux 609 fc	18,783 lux 1,746 fc	1,155 lux 107 fc
	3m	704 lux 65 fc	1,877 lux 174 fc	132 lux 12 fc
10,000K	1m	6,177 lux 574 fc	17,621 lux 1,638 fc	1,082 lux 101 fc
	3m	660 lux 61 fc	1,756 lux 163 fc	124 lux 11 fc
20,000K	1m	5,633 lux 524 fc	15,391 lux 1,431 fc	944 lux 88 fc
	3m	576 lux 54 fc	1,540 lux 143 fc	108 lux 10 fc

What's in the Box

Name	Qty
STORM 80c Lamp Head with Yoke	1
Mini ProLock Hyper Reflector	1
Mini Lantern Diffuser	1
Mini ProLock Mount Protection Cover	1
AC Power Adapter	1
AC Power Cable (4m)	1
Soft Carrying Case	1



STORM 80c Specifications

LED Chipset		BLAIR-CG
CCT		1,800K – 20,000K
Color Gamut Coverage		90%+ Rec.2020
CRI		97
TLCI		99
CQS (5600K)		96
CQS (3200K)		97
SSI (Tungsten)		88
SSI (D56)		84
TM-30 RF (Average)		96
TM-30 RG (Average)		103
Max Power Consumption		100W
Max Power Output		80W
Weather Resistance Rating		IP65
Native COB Beam Angle		60°
Included Reflector Beam Angle		35°
Operating Voltage		100V ~ 240V / 50-60 Hz
DC Adapter Output		19V/5.3A
V-Mount Battery Operating Voltage		14.4V
USB-C Power Specifications		In 20V/5A; Out 5V/0.5A
Operating Temperature		-20°C ~ 45°C / -4°F ~ 113°F
Storage Temperature		-40°C ~ 80°C / -40°F ~ 176°F
Control Methods		On-board, Sidus Link App, Sidus Link Pro App, DMX, RDM, CRMX
Data Ports		USB-C, Locking 3-Pin DMX Terminal
Firmware Upgradeable		Sidus Link, Sidus Link Pro, USB-C
Screen Type		TFT
Wireless Range	Sidus Bluetooth	≤100m / ≤262.5ft
	CRMX (TimoTwo)	≤100m / ≤262.5ft
Lamp Head Fan Noise Levels (at 1m)	Smart Mode	26.1 dBA
	High Mode	26.7 dBA
	Medium Mode	24.4 dBA
	Silent Mode	0 dBA
Dimensions	Lamp Head (Without Yoke)	10.1 x 10.4 x 14.7cm 4.0 x 4.1 x 5.8in
	Lamp Head (With Yoke)	16.7 x 22.5 x 14.7cm 6.6 x 8.9 x 5.8in
Weight	Lamp Head (Without Yoke)	1.01kg / 2.23lbs
	Lamp Head (With Yoke)	1.35kg / 2.98lbs
	AC Power Adapter	405g / 0.89lb



CF4 Fresnel Feature Sheet

Main Features

- **Compact Fresnel** with Mini ProLock Mount Designed for the STORM 80c
- Intensifies STORM 80c Daylight (5600K) Output by **5.5 Times** to **36,000 Lux** at 1 Meter
- **15° to 40° Spot-Flood Range**
- Included **Protective Carrying Case** For Storing and Transporting **both CF4 Fresnel and CF4 Barn Doors** (separately available)
- **Smooth Falloff** From Center to Edge of Output

What's in the Box

Name	Qty
CF4 Fresnel	1
Carrying Case	1

Photometrics

CCT	Dis.	15° Spot	40° Flood
1,800K	1m	24,995 lux 417 fc	8,666 lux 806 fc
	3m	2,418 lux 236 fc	998 lux 93 fc
3,200K	1m	34,625 lux 3,215 fc	11,981 lux 1,122 fc
	3m	2,417 lux 328 fc	1,399 lux 129 fc
4,300K	1m	36,592 lux 3,223 fc	12,590 lux 1,121 fc
	3m	3,472 lux 327 fc	1,452 lux 129 fc
5,600K	1m	36,000 lux 3,197 fc	12,500 lux 1,110 fc
	3m	3,512 lux 324 fc	1,459 lux 127 fc
6,500K	1m	34,723 lux 3,124 fc	12,296 lux 1,083 fc
	3m	3,423 lux 316 fc	1,436 lux 124 fc
10,000K	1m	32,264 lux 2,744 fc	11,558 lux 1,009 fc
	3m	3,197 lux 296 fc	1,340 lux 116 fc
20,000K	1m	28,920 lux 2,552 fc	10,397 lux 884 fc
	3m	2,912 lux 260 fc	1,211 lux 101 fc



Product Description

The CF4 Fresnel is a compact fresnel with a 4-inch diameter lens and Mini ProLock mount optimized for use with the STORM 80c. The CF4 Fresnel optimizes and amplifies the light output of the STORM 80c providing smooth falloff from center to edge, all with a compact form factor. Compatible with a separately available CF4 Barn Door, the CF4 Fresnel is a compact solution for users to achieve greater versatility and control of their STORM 80c's output. The CF4 Fresnel's carrying case comfortably fits the Fresnel and its Barn Doors within.

Specifications

Beam Angle	Full Spot	15°
	Full Flood	40°
Dimensions	CF4 Fresnel	Φ14.0 x 8.7cm Φ5.5 x 3.4 in
	Carrying Case	24×15×25cm 9.44× 5.9 ×9.84in
Weight	CF4 Fresnel	0.53kg / 1.17lbs
	Carrying Case	0.22kg / 0.49lbs

Sales & Shipping Information

Product Name	CF4 Fresnel
SKU	APOF056A35
UPC	6977162451169
Packing Dimensions	25.2 x 17.0 x 15.0cm 9.92 x 6.7 x 5.9in
Net Weight	0.53kg / 1.17lbs
Gross Weight	1.08kg / 2.38lbs
Carton Quantity	6 pcs
Carton Dimensions	48.0 x 39.0 x 33.5cm 18.9 x 15.4 x 13.2in
Carton Weight	7.45kg / 16.42lbs



Light Dome 40 Feature Sheet

Main Features

- 40cm (15.75in) Mini Softbox with Mini ProLock Mount
- Circular Octagonal Design for Round Reflections
- Deep Parabolic Design for Uniform Light Distribution
- High-Reflectivity Silver Inner Lining for **Maximizing Light Output**
- Quick-Release Latch Design for **Fast Deployment and Tear Down**
- 1-Stop & 2-Stop Diffusion Cloths, & 45° Light Control Grid Included
- Soft Carrying Bag Included

What's in the Box

Name	Qty
Light Dome 40	1
2-Stop Diffusion Cloth	1
1-Stop Diffusion Cloth	1
Light Control Grid	1
Carrying Bag	1

Photometrics

CCT	Dis.	STORM 80c, 1-Stop Diffusion Cloth	STORM 80c, 2-Stop Diffusion Cloth
1,800K	1m	1,640 lux 152 fc	1190 lux 111 fc
	3m	164 lux 15 fc	113 lux 11 fc
3,200K	1m	2,302 lux 214 fc	1,666 lux 155 fc
	3m	230 lux 21 fc	158 lux 15 fc
4,300K	1m	2,413 lux 224 fc	1,733 lux 161 fc
	3m	238 lux 22 fc	164 lux 15 fc
5,600K	1m	2,398 lux 223 fc	1,734 lux 161 fc
	3m	241 lux 22 fc	166 lux 15 fc
6,500K	1m	2,345 lux 218 fc	1,714 lux 159 fc
	3m	236 lux 22 fc	160 lux 15 fc
10,000K	1m	2,208 lux 205 fc	1,603 lux 149 fc
	3m	220 lux 20 fc	151 lux 14 fc
20,000K	1m	2,003 lux 186 fc	1,447 lux 134 fc
	3m	199 lux 18 fc	137 lux 13 fc



Product Description

The Light Dome 40 is a round 8-corner mini soft box with a 40cm (15.75in) light surface diameter and a Mini ProLock mount ideal for usage with the STORM 80c. Featuring a highly reflective silver lining and deep parabolic design, the Light Dome 40 gives users maximum output with uniform edge-to-edge illumination. With a quick-release latch design, the Light Dome 40 can be quickly deployed or torn down without having to individually snap support rods in place. Included with the soft box are a 1-stop diffusion cloth, 2-stop diffusion cloth, 45° light control grid, and a soft carrying bag.

Specifications

Dimensions	Open	Φ44.0 x 23.0cm 17.3 x 9.1in
	Collapsed	38.0 x 10.0 x 4.3cm 15.0 x 3.9 x 1.7in
	Carrying Bag	50.0 x 25.0 x 1.0cm 19.7 x 9.8 x 0.4in
Weight	Light Dome 40 (No Diffusion)	0.28kg / 0.62lbs
	1-Stop Diffusion	0.014kg / 0.031lbs
	2-Stop Diffusion	0.019kg / 0.042lbs
	Light Control Grid	0.038kg / 0.083lbs
	Carrying Bag	0.21kg / 0.46lbs

Sales & Shipping Information

Product Name	Light Dome 40
SKU	AA07060021
UPC	6977162451190
Packing Dimensions	45.6 x 21.8 x 7.8cm 18.0 x 8.6 x 3.1in
Net Weight	0.56kg / 1.23lbs
Gross Weight	0.80kg / 1.76lbs
Carton Quantity	8 pcs
Carton Dimensions	47.0 x 46.3 x 37.0cm 18.5 x 18.2 x 14.6in
Carton Weight	7.80kg / 19.19lbs



Lantern 30 Feature Sheet

Main Features

- 30cm (11.8in) Omnidirectional Soft Box
- Mini ProLock Mount for Secure Attachment to Mini ProLock Fixtures
- Hook-and-Loop Light Control Skirt Included
- Soft Carrying Bag Included

What's in the Box

Name	Qty
Lantern 30	1
Light Control Skirt	1
Carrying Bag	1

Photometrics

CCT	Dis.	Output with STORM 80c
1,800K	1m	686 lux 64fc
	3m	65 lux 6fc
3,200K	1m	964 lux 90 fc
	3m	91 lux 8fc
4,300K	1m	1006 lux 94 fc
	3m	94 lux 9 fc
5,600K	1m	1001 lux 93 fc
	3m	94 lux 9 fc
6,500K	1m	986 lux 92 fc
	3m	93 lux 9 fc
10,000K	1m	922 lux 86 fc
	3m	86 lux 8 fc
20,000K	1m	834 lux 80 fc
	3m	78 lux 7 fc



Product Description

The Lantern 30 is an omni-directional soft box with a 30cm (11.8in) and a Mini ProLock mount ideal for usage with the STORM 80c. The Lantern 30 provides users with the ability to omnidirectionally light environments and subjects with a soft light source. With its included hook-and-loop light control skirt, users can limit the spread of the Lantern 30's output as they see fit. The Lantern 30 comes with a soft carrying bag for easy storage and transportation.

Specifications

Dimensions	Open	Φ30.0 x 39.0cm Φ11.9 x 15.35in
	Collapsed	0.9 x 39.0cm 0.4 x 15.4in
	Carrying Bag	17.0 x 44.0cm 6.7 x 17.3in
Weight	Lantern 30 (No Skirt)	0.15kg / 0.34lbs
	Lantern 30 (With Skirt)	0.21kg / 0.48lbs
	Carrying Bag	0.03kg / 0.07lbs

Sales & Shipping Information

Product Name	Lantern 30
SKU	AA07060022
UPC	6977162451206
Packing Dimensions	41.0 x 12.0 x 12.0cm 16.0 x 4.7 x 4.7in
Net Weight	0.26kg / 0.57lbs
Gross Weight	0.61kg / 1.34lbs
Carton Quantity	12 pcs
Carton Dimensions	49.5 x 42.0 x 38.0cm 19.4 x 16.5 x <u>15.0in</u>
Carton Weight	12.00kg / 26.45lbs



STORM 80c Accessory Data Book

STORM 80c Handheld Bracket

Product Description

The STORM 80c Handheld Bracket allows users to use the STORM 80c on the run. It features a 3/8-16in thumbscrew on the top of the handle that secures to a STORM 80c lamp head and has a V-Mount receiver to mount V-Mount batteries or USB battery banks using the Aputure V-Mount Bracket for Power Bank. This Handheld Bracket also includes a coiled D-Tap to 5.5mm DC Barrel Power Cable and features a baby pin receiver at the base of the handle.

What's in the Box

Name	Qty
STORM 80c Handheld Bracket	1
D-Tap to 5.5mm DC Barrel Power Cable	1

STORM 80c Bowens Mount

Adapter

Product Description

The STORM 80c Bowens Mount Adapter is a metal accessory mount adapter that allows users to pair traditional Bowens Mount accessories to Mini ProLock, making them compatible with the STORM 80c. Recommended Aputure Bowens Mount accessories to adapt for use with the STORM 80c via this adapter include the Light Dome Mini III, Light Dome SE, and Lantern.

What's in the Box

Name	Qty
STORM 80c Bowens Mount Adapter	1

Sidus One DMX 2-Way Splitter Cable

Product Description

The Aputure Sidus One DMX 2-Way Splitter Cable is a 5-Pin DMX adapter that gives users the ability to hardline a Sidus One or STORM 80c into a DMX Network. It offers a male 5-Pin DMX connector, female 5-Pin DMX connector, and a 3-pin push-pull connector found on the Sidus One and STORM 80c.

What's in the Box

Name	Qty
Sidus One DMX 2-Way Splitter Cable	1



Sales & Shipping Information

Product Name	STORM 80c Handheld Bracket
SKU	APOM062A39
UPC	6977162451176
Packing Dimensions	22.4 x 11.2 x 5.5cm / 8.82 x 4.41 x 2.16in
Net Weight	0.32kg / 0.71lbs
Gross Weight	0.48kg / 1.06lbs
Carton Quantity	28 pcs
Carton Dimensions	49x 42.0 x 27.5cm / 19.29 x 16.54 x 10.82in
Carton Weight	14.43kg / 31.8lbs



Sales & Shipping Information

Product Name	STORM 80c Bowens Mount Adapter
SKU	APOT013A3B
UPC	6977162451183
Packing Dimensions	14.4x13.4x3.4cm / 5.7 x 5.3 x 1.3in
Net Weight	0.13kg / 0.29lbs
Gross Weight	0.17kg / 0.37lbs
Carton Quantity	48 pcs
Carton Dimensions	41.5x36.5x31.5cm / 16.3 x 14.4 x 12.4in
Carton Weight	9.70kg / 21.38lbs



Sales & Shipping Information

Product Name	Sidus One DMX 2-Way Splitter Cable
SKU	APRO316A34
UPC	6971842189045
Packing Dimensions	18.4*7.4*5.0cm / 7.24 x 2.91 x 1.97in
Net Weight	0.130kg / 0.29lb
Gross Weight	0.130kg / 0.29lb
Carton Quantity	32 pcs
Carton Dimensions	38.7 x 31.9 x 22.8cm / 15.24 x 12.56 x 8.98in
Carton Weight	4.66kg / 10.27lbs



STORM 80c Accessory Data Book

Baby Pin to Anti-Rotating 3/8in Screw Adapter

Product Description

The Aputure Baby Pin to Anti-Rotating 3/8in Screw Adapter allows users to adapt the STORM 80c's 3/8-16in Threads to a full-sized baby pin. This gives users the option to rig the STORM 80c using an all-metal baby pin instead of the standard female baby pin yoke the light originally comes with.

What's in the Box

Name	Qty
Baby Pin to Anti-Rotating 3/8in Screw Adapter	1



Sales & Shipping Information

Product Name	Baby Pin to Anti-Rotating 3/8in Screw Adapter
SKU	AS0706012T
UPC	6977162453729
Packing Dimensions	13x3.5x2.6cm 5.12x1.38x1.02in
Net Weight	0.16kg / 0.36lbs
Gross Weight	0.17kg / 0.39lbs
Carton Quantity	108
Carton Dimensions	42.6x19.5x25cm 16.77x7.68x9.84in
Carton Weight	19.1kg / 42.1lbs

Locking 5.5mm DC to 5.5mm DC Barrel Extension Cable (3m)

Product Description

The Aputure Locking 5.5mm DC to 5.5mm DC Barrel Extension Cable (3m) is a collar-locking 3-meter DC power extension cable that allows users to securely extend the connection between the STORM 80c and its AC power adapter.

What's in the Box

Name	Qty
Locking 5.5mm DC to 5.5mm DC Barrel Extension Cable (3m)	1



Sales & Shipping Information

Product Name	Locking 5.5mm DC to 5.5mm DC Barrel Extension Cable (3m)
SKU	APE0300AX1
UPC	6971842188390
Packing Dimensions	15.0 x 9.5 x 6.5cm / 6.02 x 3.74 x 2.56in
Net Weight	0.26kg / 0.59lbs
Gross Weight	0.31kg / 0.71lbs
Carton Quantity	48pcs
Carton Dimensions	47.0 x 40.0 x 28.4cm / 18.5 x 15.7 x 11.2 in
Carton Weight	16.00kg / 36.60lbs

D-Tap to 5.5mm DC Barrel Power Cable

Product Description

The Aputure D-Tap to 5.5mm DC Barrel Power Cable is a coiled D-Tap to 5.5mm DC Barrel adapter cable that allows users to power their STORM 80c off of a V-Mount battery. This gives users more flexibility when their fixture's power source is not tethered to an AC outlet.

What's in the Box

Name	Qty
D-Tap to 5.5mm DC Barrel Power Cable	1



Sales & Shipping Information

Product Name	D-Tap to 5.5mm DC Barrel Power Cable
SKU	AS0706013Y
UPC	6977162453965
Packing Dimensions	11.0 x 1.5 x 18.0cm / 4.3 x 0.6 x 7.1in
Net Weight	0.05kg / 0.12lbs
Gross Weight	0.07kg / 0.15lbs
Carton Quantity	56 pcs
Carton Dimensions	18.0 x 43.0 x 31.5cm / 7.1 x 16.9 x 12.4in
Carton Weight	4.00kg / 9.16lbs



STORM 80c Accessory Data Book

CF4 Barn Doors

Product Description

The Aputure CF4 Barn Doors is a light control attachment designed to mount to the front of the CF4 Fresnel. The 8-leaf doors allow users to shape and cut the light at the lamp. The CF4 Barn Doors also incorporates a holder for a 5" metal scrim to control light output.

What's in the Box

Name	Qty
CF4 Barn Doors	1



Sales & Shipping Information

Product Name	CF4 Barn Doors
SKU	AA07060068
UPC	6977162451213
Packing Dimensions	27 × 17.4 × 5.9cm 10.63 × 6.85 × 2.32 in
Net Weight	0.38kg / 0.83lbs
Gross Weight	0.55kg / 1.21lbs
Carton Quantity	12
Carton Dimensions	54×33.5×27.5cm 21.2 × 12.2 × 10.8 in
Carton Weight	7.35kg / 16.1lbs