100% recycled material used for external cassette

+40% of DYMO® labels are produced* using „Water based solvents".

DYMO® high quality labels are made in Belgium

D1

D1 Standard Polyester Labels

For hundreds of tasks around the office or home office, such as filing, storage and asset tracking.
Temperature rating: -18°C to 90°C

D1 STANDARD LABELS (7 m)	6 mm	9 mm	12 mm	19 mm
ABC	S0720780	S0720680	S0720530	S0720830
ABC	S0720770	S0720670	S0720500	S0720820
ABC	S0720790	S0720730	S0720580	S0720880
ABC	-	S0720710	S0720560	S0720860
ABC	-	S0720740	S0720590	S0720890
ABC	-	S0720720	S0720570	S0720870
ABC	-	-	S0720610	S0720910
ABC	-	S0720690	S0720540	S0720840
ABC	-	-	S0720510	–
ABC	-	-	S0720600	–
ABC	-	S0720700	S0720550	S0720850
ABC	-	-	S0720520	–
D1 STANDARD MULTIPACKS (7 m)	**6 mm**	**9 mm**	**12 mm**	**19 mm**
ABC	-	2093096	2093097	2093098





D1 Durable Vinyl Labels

Industrial strength adhesive helps to ensure labels stay stuck to a variety of surfaces.
Temperature rating: -40˚C to 80˚C

D1 DURABLE LABELS (3 m)	12 mm
ABC	1978366
ABC	1978365
ABC	1978367
D1 DURABLE LABELS (5.5 m)	**12 mm**
ABC	1978364





D1 Permanent Polyester Labels

Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins and more.

Temperature rating: -40˚C to 150˚C*

D1 PERMANENT POLYESTER (5.5 m)	12 mm	19 mm
ABC	S0718060	S0718050

*depends on surface





D1 Flexible Nylon Labels

Specifically designed for curved surfaces and wire and cable marking.

Temperature rating: -40˚C to 60˚C

D1 FLEXIBLE NYLON (3.5 m)	12 mm	19 mm
ABC	S0718040	S0718070





The DYMO® high quality labels are made in Belgium

DYMO
newell BRANDS

© 2021 Newell Brands

This information is being provided for general information purposes and the compliance standards and certifications referenced herein are based on current standards which are subject to change.

ALWAYS USE
UTILISEZ TOUJOURS
AUTHENTIC
AUTHENTIQUE
DYMO
LABELS
ÉTIQUETTES