

GiuliettaX

PL2SVX



TECHNICAL FEATURES

2 L58E groups compatible with
LELIT58 barista tools

Double HX System for group heating with
thermosyphonic circulation

Rotative pump

LCD display with black background

Possibility to activate the pre-infusion, the cleaning
cycle and the notification for the water filter change

Programmable automatic dosing on each group

Temperature displayed in degrees
Celsius or Fahrenheit

Operating temperatures programmable
thanks to the LTS (LELIT Thermal Stability)

Dose counter for each group and for single button

Active Coffee delivery timer and ECO Mode

Double manometer for pump/steam pressure

Water supply and direct discharge

Stainless steel appliance body with textured
cup warmer rack and removable side panels

Anti-burn multidirectional steam and
hot water wands

Double keyboard for coffee delivery

Mug friendly

Adjustable feet

Two groups coffee machine
with exceptional performance,
configurable to efficiently
meet the needs of every
professional user.

The machine is versatile,
performing, highly reliable
and easy to use and
maintain.

Copper boiler: 10 l

Dimensions LxDxH: 58x56x46 cm

Weight: 47 kg

DELIVERED WITH

2 LELIT58 2-ways filterholder with classic
polished black handle and Coffee Slide spout

LELIT58 1 dose filter (9-11 g), IMS

2 LELIT58 2 doses filter (14-18 g), IMS

LELIT58 blind filter, IMS

Tamper

2 cup racks

Small brush with nylon bristles

PL2SVX-EU	230 V 50 Hz Plug Type E+F
PL2SVX-AUS-4180	220-240 V 50/60 Hz Plug Type I
PL2SVX-CUS	120 V 60 Hz Plug Type B
PL2SVX-UK	220-240 V 50/60 Hz Plug Type G