



DELL EMC NETWORKING S5200-ON SERIES SWITCHES

High-performance, open networking 25GbE top-of-rack and 100GbE spine/leaf switches

The S5200-ON 25/100GbE fixed switches comprise Dell EMC's latest disaggregated hardware and software data center networking solutions, providing state-of-the-art, high-density 25/100GbE ports and a broad range of functionality to meet the growing demands of today's data center environment. These innovative, next-generation open networking switches offer optimum flexibility and cost-effectiveness for web 2.0, enterprise, mid-market and cloud service provider with demanding compute and storage traffic environments.

The S5200-ON is a complete family of switches: 48-port 25GbE/100GbE ToR switch, 96-port 25GbE/100GbE Middle of Row (MoR)/End of Row (EoR) switch, and a 32-port 100GbE Multi-Rate Spine/Leaf switch. From the traditional 48-port ToR, to the high density S5296F-ON for Middle of Row deployments, the S5200-ON series offers performance and flexibility for a variety of network designs.

In addition to 100GbE Spine/Leaf deployments, the S5232F-ON can also be used in high density deployments using breakout cables to achieve up to 128 10GbE or 128 25GbE ports.

Using industry-leading hardware and a choice of Dell EMC's OS10 or select 3rd party network operating systems and tools, the S5200-ON switches incorporate multiple architectural features that optimize data center network flexibility, efficiency and availability, including IO panel to PSU or PSU to IO panel airflow for hot/cold aisle environments, redundant, hot-swappable power supplies and fans and deliver non-blocking performance for workloads sensitive to packet loss.

Priority-based flow control (PFC), data center bridge exchange (DCBX) and enhanced transmission selection (ETS) make the S5200-ON family ideally suited for DCB environments.

Dell EMC Networking S5200-ON switches support the open source Open Network Install Environment (ONIE) for zero touch installation of Dell EMC's OS10 networking operating system, as well as alternative network operating systems.

Key applications

- Organizations looking to enter the software-defined data center era with a choice of networking technologies designed to maximize flexibility
- High-density 10/25GbE ToR server aggregation in high-performance data center environments at the desired fabric speed with the S5248F-ON or S5296F-ON
- Small-scale Fabric implementation via the S5232F-ON switch in leaf and spine along with S5248F-ON 1/10/25GbE ToR switches enabling cost-effective aggregation of 10/25/40/50/100 uplinks

- Multi-functional 10/25/40/50/100GbE switching in High Performance Computing Clusters or other business-sensitive deployments requiring the highest bandwidth.
- iSCSI deployments, including DCB converged lossless transactions
- Single-pass VXLAN routing (future software release)

Key features

- 1 or 2RU high-density ToR switches with up to 48 or 96 ports of 25GbE or 32 ports of 100GbE
- Multi-rate 100GbE ports support 10/25/40/50/100GbE
- Scalable L2 and L3 Ethernet switching with QoS and a full complement of standards-based IPv4 and IPv6 features, including OSPF and BGP routing support
- Line-rate performance via non-blocking switch fabrics: 3.2Tbps on S5296F-ON and S5232F-ON, and 2.0Tbps on S5248F-ON
- L2 multipath support via Virtual Link Trunking (VLT) and Routed VLT support
- VXLAN gateway functionality support for bridging and routing the non-virtualized and the virtualized overlay networks with line rate performance (hardware only)
- Support for OS10 Enterprise Edition
- Converged network support for DCB, with priority flow control (802.1Qbb), ETS (802.1Qaz), DCBx and iSCSI TLV support
- Routable RoCE to enable convergence of compute and storage on Leaf/Spine Fabric
- IO panel to PSU airflow or PSU to IO panel airflow Redundant, hot-swappable power supplies and fans on most models
- Supports the open source Open Network Install Environment (ONIE) for zero touch installation of alternate network operating systems
- L2 VXLAN (Static VXLAN with VLT, BGP EVPN)
- Tool-less enterprise ReadyRails™ mounting kits reducing time and resources for switch rack installation
- Power-efficient operation and Dell Fresh Air 2.0 compliant up to 45°C helps reduce cooling costs in temperature constrained deployments

Key features with Dell EMC Networking OS10

- Consistent DevOps framework across compute, storage and networking elements
- Standard networking features, interfaces and scripting functions for legacy network operations integration
- Standards-based switching hardware abstraction via Switch Abstraction Interface (SAI)
- Pervasive, unrestricted developer environment via Control Plane Services (CPS)
- OS10 Enterprise Edition software enables Dell EMC layer 2 and 3 switching and routing protocols with integrated IP services, quality of service, manageability and automation features
- Leverage common open source tools and best practices (data models, commit rollbacks*)
- Increase VM Mobility region by stretching L2 VLAN within or across two DCs with unique VLT capabilities
- Scalable L2 and L3 Ethernet Switching with QoS, ACL and a full complement of standards based IPv4 and IPv6 features including OSPF, BGP and PBR
- Enhanced mirroring capabilities including local mirroring, Remote Port Mirroring (RPM), and Encapsulated Remote Port Mirroring (ERPM).
- Converged network support for Data Center Bridging, with priority flow control (802.1Qbb), ETS (802.1Qaz), DCBx and iSCSI TLV

*Roadmap

	S5248F-ON	S5296F-ON	S5232F-ON
Ports	48xSFP28 2xQSFP28-DD 4xQSFP28	96xSFP28 8xQSFP28	32xQSFP28 2xSFP+
Max 10GbE density	80	128	128
Max 25GbE density	80	128	128
Max 40GbE density	8	8	32
Max 50GbE density	16	16	64
Max 100GbE density	8	8	32
Switching capacity	2.0Tbps	3.2Tbps	3.2Tbps
Throughput	1.5Bpps	2.4Bpps	2.4Bpps
Latency (nano sec)	847	850	877
1588v2 PTP timing (hardware)	●	●	●
CPU Memory	16GB	16GB	16GB
SSD	64GB	64GB	64GB
Packet Buffer	32MB	32MB	32MB
Maximum power	602W	835W	635W
Typical power	400W	640W	445W
Maximum current	7A@110VAC / 3.5A@220VAC	10A@110VAC / 5A@220VAC	7A@110VAC / 3.5A@220VAC
Fan modules	4	4	4
Form Factor	1RU	2RU	1RU
Dimensions	17.1"Wx18.1"Dx1.7"H 43.4Wx46.0Dx4.4H (cm)	17.4"Wx20.1"Dx3.4"H 44.2Wx51.1Dx8.7H (cm)	17.1"Wx18.1"Dx1.7"H 43.4Wx46.0Dx4.4H (cm)
Weight	9.7kg (21.3lbs)	15.1kg (33.2lbs)	9.8kg (21.6lbs)
Max thermal output	2054 BTU/h	2894 BTU/h	2167 BTU/h

Product	Description
S5200-ON	S5248F, 48x 25GbE SFP28 + 2x 200GbE QSFP28-DD + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, OS10 Enterprise Edition S5248F, 48x 25GbE SFP28 + 2x 200GbE QSFP28-DD + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, OS10 Enterprise Edition S5248F, 48x 25GbE SFP28 + 2x 200GbE QSFP28-DD + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, NO-OS S5248F, 48x 25GbE SFP28 + 2x 200GbE QSFP28-DD + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, NO-OS S5248F, 48x 25GbE SFP28 + 2x 200GbE QSFP28-DD + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, OS10 Enterprise Edition, TAA S5248F, 48x 25GbE SFP28 + 2x 200GbE QSFP28-DD + 4x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, OS10 Enterprise Edition, TAA S5296F, 96x 25GbE SFP28 + 8x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, OS10 Enterprise Edition S5296F, 96x 25GbE SFP28 + 8x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, OS10 Enterprise Edition S5296F, 96x 25GbE SFP28 + 8x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, NO-OS S5296F, 96x 25GbE SFP28 + 8x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, NO-OS S5296F, 96x 25GbE SFP28 + 8x 100GbE QSFP28, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, OS10 Enterprise Edition, TAA S5296F, 96x 25GbE SFP28 + 8x 100GbE QSFP28, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, OS10 Enterprise Edition, TAA S5232F, 32x QSFP28 + 2x 10GbE SFP+, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, OS10 Enterprise Edition S5232F, 32x QSFP28 + 2x 10GbE SFP+, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, OS10 Enterprise Edition S5232F, 32x QSFP28 + 2x 10GbE SFP+, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, NO-OS S5232F, 32x QSFP28 + 2x 10GbE SFP+, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, NO-OS S5232F, 32x QSFP28 + 2x 10GbE SFP+, 2x AC PSU, Fan modules, I/O Panel to PSU Airflow, OS10 Enterprise Edition, TAA S5232F, 32x QSFP28 + 2x 10GbE SFP+, 2x AC PSU, Fan modules, PSU to I/O Panel Airflow, OS10 Enterprise Edition, TAA
Redundant power supplies	AC Power Supply, IO Panel to PSU Airflow AC Power Supply, PSU to IO Panel Airflow DC Power Supply, IO Panel to PSU Airflow (available as custom kit) DC Power Supply, PSU to IO Panel Airflow (available as custom kit)
Fans	Fan module, IO Panel to PSU Airflow Fan module, PSU to IO Panel Airflow
Optics	Transceiver, 2x100GbE, 2xSR4, QSFP28-DD Transceiver, 2x100GbE, 2xPSM4-IR, QSFP28-DD Transceiver, 2x100GbE, 2xCWDM4, QSFP28-DD Transceiver, 100GbE, SR4 QSFP28 Transceiver, 100GbE, PSM4 (500m) QSFP28 Transceiver, 100GbE, CWDM4 (2Km) QSFP28 Transceiver, 100GbE, LR4 QSFP28 Transceiver, 40GbE, SR4 optic QSFP+ Transceiver, 40GbE, BiDi optic QSFP+ (Duplex) Transceiver, 40GbE, SM4 optic QSFP+ (Duplex) Transceiver, 40GbE, LM4 optic QSFP+ (Duplex) Transceiver, 40GbE, PSM4 10Km, QSFP+ Transceiver, 40GbE, LR4 optic QSFP+ Transceiver, 40GbE, ER4 optics QSFP+ Transceiver, 25GbE, SR, NOF SFP28 Transceiver, 25GbE, LR, SFP28 Transceiver, 10GbE, SR SFP+, short reach Transceiver, 10GbE, LR SFP+, long reach Transceiver, 10GbE, ER SFP+, extended reach Transceiver, 10GbE, ZR SFP+ extra extended reach 10G, Transceiver, 10GBASE-T use with QSA in QSFP+ port, 30m reach on CAT6a/7 Transceiver, 1GbE, SX SFP Transceiver, 1GbE, LX SFP Transceiver, 1GbE, ZX SFP Transceiver, 1GbE, 10km, BiDi SFP Transceiver, 1GbE, 40km, BiDi SFP Transceiver, 1GbE, 80km, BiDi SFP Transceiver, 1GbE, 1000BASE-T, Gen2, SFP

Product	Description
Cables	100GbE, 4x25GbE, QSFP28 to 4xSFP28, passive DAC 100GbE, QSFP28 to QSFP28, active optical 100GbE, QSFP28 to QSFP28, passive DAC 100GbE, 2x50GbE, 2xQSFP to 2xQSFP28, passive DAC, breakout 40GbE, QSFP+ to QSFP+, active optical 40GbE, QSFP+ to QSFP+, passive DAC 40GbE, MTP to 4xLC optical breakout 40GbE, 4x10GbE, QSFP+ to 4xSFP+, passive DAC
Cable management	Z9100 Cable Breakout Kit, MTP to LC (1RU 64-port LC over MMF) Z9100 Cable Breakout Kit, MTP to LC (1RU 64-port LC over SMF)

Technical specifications

Physical

1 RJ45 console/management port with RS232 signaling

S5248F-ON: 48x25GbE SFP28 + 4x 100GbE QSFP28 + 2x 2x100GbE QSFP28-DD

S5296F-ON: 96x25GbE SFP28 + 8x 100GbE QSFP28

S5232F-ON: 32x100GbE QSFP28 ports + 2xSFP+ 10GbE

Environmental

Power supply: 100–240 VAC 50/60 Hz

Max Operating specifications:

AC Max. Operating specifications:

Operating temperature: 32° to 113°F (0° to 45°C)

Operating humidity: 5 to 90% (RH), non-condensing

Max. Non-operating specifications:

Storage temperature: –40° to 158°F (–40° to 70°C)

Storage humidity: 5 to 90% (RH), non-condensing

Fresh air Compliant to 45°C

Redundancy

Hot swappable redundant power

Hot swappable redundant fans

Performance

Packet buffer memory: 32MB

CPU memory: 16GB

MAC addresses: 160K

ARP table: 128K

IPv4 routes: 128K

IPv6 routes: 64K

Multicast hosts: 32K

Link aggregation: 16 links per group, 128 groups

Layer 2 VLANs: 4K

MSTP: 64 instances

LAG load balancing: Based on layer 2, IPv4 or IPv6 headers

IEEE Compliance

802.1AB LLDP

TIA-1057 LLDP-MED

802.3ad Link Aggregation

802.1D Bridging, STP

802.1p L2 Prioritization

802.1Q VLAN Tagging

802.1Qbb PFC

802.1Qaz ETS

802.1X Network Access Control

802.3ac Frame Extensions for VLAN Tagging

802.3x Flow Control

Layer2 Protocols

802.1D Compatible

802.1p L2 Prioritization

802.1Q VLAN Tagging

802.1s MSTP

802.1w RSTP

802.1t RPVST+

VLT (Virtual Link Trunking)

VRRP Active/Active

RSTP & RPVST+

Port Mirroring on VLT ports

DCB, iSCSI, FSB on VLT

RPM/ERPM over VLT

VLT loss upgrade

RFC Compliance

768 UDP

793 TCP

854 Telnet

959 FTP

1321 MD5

1350 TFTP

2474 Differentiated Services

2698 Two Rate Three Color Marker

3164 Syslog

4254 SSHv2

General IPv4 Protocols

791 IPv4

792 ICMP

826 ARP

1027 Proxy ARP

1035 DNS (client)

1042 Ethernet Transmission

1191 Path MTU Discovery

1305 NTPv4

1519 CIDR

1812 Routers, Static Routes

1858 IP Fragment Filtering

2131 DHCPv4 (server and relay)

5798 VRRPv3

3021 31-bit Prefixes

1812 Requirements for IPv4 Routers

1918 Address Allocation for Private Internets

2474 Diffserv Field in IPv4 and Ipv6 Headers

2597 Assured Forwarding PHB Group

3195 Reliable Delivery for Syslog

3246 Expedited Forwarding PHB Group

VRF (BGPv4/v6)

General IPv6 Protocols

1981 Path MTU for IPv6

2372 IPv6 Addressing

2460 IPv6 Protocol Specification

2461 Neighbor Discovery

2462 Stateless Address AutoConfig

2711 IPv6 Router alert

2463 ICMPv6

2464 Ethernet Transmission

2675 IPv6 Jumbograms

3484 Default Address Selection

3493 Basic Socket Interface

4291 Addressing Architecture

3542 Advanced Sockets API

3587 Global Unicast Address Format

4291 IPv6 Addressing

2464 Transmission of IPv6 Packets over Ethernet Networks

2711 IPv6 Router Alert Option

4007 IPv6 Scoped Address Architecture

4213 Transition Mechanisms for IPv6 Hosts and Routers

3315 DHCPv6 Server & Relay

IPv6 Static Routes

OSPF

1745 OSPF/BGP interaction

1765 OSPF Database overflow

2154 OSPF with DigitalSignatures

2328 OSPFv2

5340 OSPF for IPv6 (OSPFv3)

2370 Opaque LSA

3101 OSPF NSSA

4552 OSPFv3 Authentication

Multicast

4541 IGMPv1/v2/v3 and MLDv1/v2 Snooping

Security

2865 RADIUS

3162 Radius and IPv6

3579 Radius support for EAP

3580 802.1X with RADIUS

3826 AES Cipher in SNMP

1492 TACACS (Authentication, Accounting)

Control Plane, VTY & SNMP ACLs

IP Access Control Lists

BGP

1997 Communities

2385 MD5

2439 Route Flap Damping

2796 Route Reflection

2918 Route Refresh

3065 Confederations

4271 BGP-4

2545 BGP-4 Multiprotocol Extensions for IPv6 Inter-Domain Routing

2858 Multiprotocol Extensions

4360 Extended Communities

4893 4-byte ASN

5396 4-byte ASN Representation

5492 Capabilities Advertisement

draft-ietf-idr-add-paths-04.txt ADD PATH

Linux Distribution

Debian Linux version 9

Linux Kernel 4.9

Network Management and Monitoring

SNMPv1/2c

IPv4/IPv6 Management support (Telnet, FTP, TACACS, RADIUS, SSH, NTP)

Syslog

Port Mirroring

RPM/ERPM

3176 SFlow

Support Assist (Phone Home)

RestConf APIs (Layer 2 features)

XML Schema
 CLI Commit (Scratchpad)
 Uplink Failure Detection
 Object Tracking
 Bidirectional Forwarding Detection (BFD)
 Automation
 Control Plane Services APIs
 Linux Utilities and Scripting Tools
 CLI Automation (Multiline Alias)
 Zero Touch Deployment (ZTD)
 Ansible, Puppet, Chef, SaltStack
 8040 RESTCONF APIs (L3)

Quality of Service

Prefix List
 Route-Map
 Rate Shaping (Egress)
 Rate Policing (Ingress)
 Scheduling Algorithms
 Round Robin
 Weighted Round Robin
 Deficit Round Robin
 Strict Priority
 Weighted Random Early Detect

Data center bridging

802.1Qbb Priority-Based Flow Control
 802.1Qaz Enhanced Transmission Selection (ETS)
 Explicit Congestion Notification
 Data Center Bridging eXchange (DCBx)
 DCBx Application TLV (iSCSI, FCoE)
 RoCEv2
 Software Defined Networking
 OpenFlow 1.3 (Native)

MIBS

IP MIB
 IP Forward MIB
 Host Resources MIB
 IF MIB
 LLDP EXT1/3 MIB
 Entity MIB
 LAG MIB
 Dell-Vendor MIB
 TCP MIB
 UDP MIB
 SNMPv2 MIB
 ETHERLIKE-MIB
 SFLOW-MIB
 PFC-MIB

Regulatory compliance

Safety

UL/CSA 60950-1, Second Edition
 EN 60950-1, Second Edition
 IEC 60950-1, Second Edition Including All National
 Deviations and Group Differences
 EN 60825-1 Safety of Laser Products Part 1:
 Equipment Classification Requirements and User's
 Guide
 EN 60825-2 Safety of Laser Products Part 2: Safety
 of Optical Fibre Communication Systems
 FDA Regulation 21 CFR 1040.10 and 1040.11

Emissions

Australia/New Zealand: AS/NZS CISPR 22: 2006,
 Class A
 Canada: ICES-003, Issue-4, Class A
 Europe: EN 55022: 2006+A1:2007 (CISPR 22:
 2006), Class A
 Japan: VCCI V3/2009 Class A
 USA: FCC CFR 47 Part 15, Subpart B:2011, Class A

Immunity

EN 300 386 V1.4.1:2008 EMC for Network
 Equipment
 EN 55024: 1998 + A1: 2001 + A2: 2003
 EN 61000-3-2: Harmonic Current Emissions
 EN 61000-3-3: Voltage Fluctuations and Flicker
 EN 61000-4-2: ESD
 EN 61000-4-3: Radiated Immunity
 EN 61000-4-4: EFT
 EN 61000-4-5: Surge
 EN 61000-4-6: Low Frequency Conducted Immunity

RoHS

All S Series components are EU RoHS compliant.

Certifications

Available with US Trade Agreements Act (TAA)
 compliance
 USGv6 Host and Router Certified on Dell
 Networking OS 9.5 and greater
 IPv6 Ready for both Host and Router
 UCR DoD APL (core and distribution ALSAN switch)

Warranty

1 year return to depot

IT Lifecycle Services for Networking

Experts, insights and ease

Our highly trained experts, with innovative tools and proven processes, help you transform your IT investments into strategic advantages.



Plan & Design

Let us analyze your multivendor environment and deliver a comprehensive report and action plan to build upon the existing network and improve performance.



Deploy & Integrate

Get new wired or wireless network technology installed and configured with ProDeploy. Reduce costs, save time, and get up and running fast.



Educate

Ensure your staff builds the right skills for long-term success. Get certified on Dell EMC Networking technology and learn how to increase performance and optimize infrastructure.



Manage & Support

Gain access to technical experts and quickly resolve multivendor networking challenges with ProSupport. Spend less time resolving network issues and more time innovating.



Optimize

Maximize performance for dynamic IT environments with Dell EMC Optimize. Benefit from in-depth predictive analysis, remote monitoring and a dedicated systems analyst for your network.



Retire

We can help you resell or retire excess hardware while meeting local regulatory guidelines and acting in an environmentally responsible way.

Learn more at
DellEMC.com/Services

Learn more at DellEMC.com/Networking