

Rittal – The System.

Faster – better – everywhere.

PDU switched – DK 7979.310

Date : Jul 28, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



PDU switched – DK 7979.310

created: 28.07.2021 on www.rittal.com/com-en



Product description

Description:	High-end power distribution in a compact design for IT network and server racks. With switching function and power measurement at the infeed or per phase.
Benefits:	For vertical mounting, it may be attached in the zero-U space of the Rittal VX IT or TS IT rack with no need for tools Colour coding of phases and fuse circuits (L1=pink, L2=black, L3=white) Tool-free divider kit for VX IT PDU self-supplied, no external power supply required Measurement accuracy $\pm 1\%$ (kWh) to EN 62 053-21 Programmable startup behaviour following voltage recovery (on/off/last status) Programmable switching behaviour (time/programmable logic) Integral real-time clock with battery buffering (max. 10 years, battery replaceable) Integral electromagnetic buzzer for acoustic alarms Adjustable limit values (warning/alarm) for voltage, current, output Operating hours meter, total and cyclical, resettable
Technical specifications:	Display/controller unit in the PDU enclosure rotatable through 180° and replaceable Integral, fully-redundant power pack, power supply from all phases Error-tolerant PDU power supply redundant across all phases Voltage V, current A, frequency Hz Active power, active energy, apparent power, apparent energy Power factor (cosPhi) and phase angle Zero conductor current measurement/load imbalance detection Fuse monitoring for PDUs with integral fuse Monitoring of the optionally available overvoltage protection Bright TFT display, 128 x 128 pixels (RGB) with back-lighting and energy-saving mode to display output data and basic PDU configuration Position sensors for display rotation and correct PDU representation on the website Multi-colour LEDs (green/amber/red) to indicate switching states and warning/alarm limits per phase or infeed Power LED to indicate voltage Power-saving design, minimal intrinsic power consumption
Measurement functions:	Emergency power supply to PDU web server via PoE, sequential disconnection of the outputs Switching function per output slot Avoids overload peaks: Sequential activation of the outputs following voltage recovery

Relay states are saved even in the event of a power failure
 Bistable relays: Low current consumption and high switching capacity, also suitable for higher starting currents up to max. 300 A
 Grouping: Joint switching of multiple outputs
 Measurement per phase or infeed
 Powerful CPU (ARM Cortex A8)
 Digital input (floating contact)
 Additional alarm output/relay output (changeover contact)
 Additional alarm output/relay output (changeover contact)

Material:	Aluminium section, black anodised Slots: Plastic
Protection category IP to IEC 60 529:	IP 20
Standards:	EN 62368-1 EN 61000-3 EN 61000-4 EN 61000-6 EN 62053-21
Directives:	EMC Directive 2014/30/EU Low Voltage Directive 2014/35/EU
Supply includes:	Assembly parts
Options:	Type 3 overvoltage protection with interchangeable arresters while operational, with status monitoring, suitable for integration into PDU enclosure Residual current measurement (type B) per infeed/phase/fuse Monitoring of the optionally available overvoltage protection CMC III CAN bus sensors may be connected for ambient monitoring, max. 8 sensors Other enclosure colours are available

Product description

Variant:	Measurement per phase, switching function per output
Sockets:	12 x C 13 1 x C 19
To fit:	Enclosure type: VX IT enclosure frame Enclosure type: VX IT 19" mounting angles Height: ≥ 1200 mm Height: ≥ 1200 mm
Dimensions:	Width: 44 mm Depth: 70 mm Length: 845 mm
Rated operating voltage:	230 V (AC)
Infeeds:	Qty.: 1 Phases per infeed: 1~

Length of connection cable:	3 m
Ambient conditions:	Operating temperature: +5 °C...+50 °C Storage temperature: -20 °C...+70 °C Ambient humidity (non-condensing): 10 % - 95 %
Type of electrical connection:	CEE
Rated current (max.):	16 A
Output:	3.7 kW
Interfaces:	Fully redundant Ethernet interface 10/100/1000 Mbit/s (2x RJ45, 1x with PoE) USB 2.0 port (USB-A) for mass configuration, firmware updates & data logging CAN bus interface (RJ 45) for a maximum of 8 ambient sensors Serial interface RS232 (RJ12) for LTE unit, scripting, CLI Use of own certificates/TLS 1.2 E-mail forwarding in case of alarm (SMTP) User administration including rights management LDAP(S)/Radius/Active Directory connection Syslog server connection (max. 2 servers) Fully redundant monitoring via 2nd network Network protocol: Web server (HTTP, HTTPS, SSL) SSH, Telnet, NTP Network protocol: TCP/IP v4 & v6, DHCP, DNS Network protocol: SNMP v1, v2c & v3, Modbus/TCP, OPC-UA Network protocol: MIB for linking into 3rd party DCIM software Network protocol: FTP/SFTP (update/file transfer)
Packs of:	1 pc(s).
Weight/pack:	3.56 kg
Copper weight (kg per piece):	0
EAN:	4028177947856
Customs tariff number:	85366990
ETIM 7.0:	EC000330
ETIM 6.0:	EC000330
eCl@ss 8.0/8.1:	27142604
eCl@ss 6.0/6.1:	27142604
Product description:	PDU switched 16A/1P CEE 12xC13+1xC19, DK PDU switched, Compact basic power distributor incl. energy measurement per phase, switching function for each output slot, with network interface and display

Approvals

Certificates:	EAC
----------------------	-----

Declarations:	Declaration of conformity
----------------------	---------------------------