




PUR is the abbreviation for polyurethane.
The material PUR is a thermoplastic elastomer (TPE)
and has special properties.

The industrial market prefer cables with PUR cable jacket
because of its many advantages.

PUR advantages:
abrasion-resistant, suitable for drag chains, tensile strength, oil-resistant,
pull tight, notch-resistant, bend-resistant, impact-tough,
cold-flexible, heat-resistant, UV-resistant, hydrolysis resistant;

Suitable for outdoor use.

Not suitable for buried installation,
please pay attention to the legal regulations and
use cable tubes / ducts for such installations.

- Connections: RJ45 plug to RJ45 plug
- Compatible with: 10GBASE-T, 1000BASE-T and below
- Transmission frequency cable up to: 600 MHz
- Transmission frequency plug up to: 500 MHz
- Bandwidth up to: 10 Gbit/s
- Pin assignment: EIA/TIA 568B
- Cable specification: Cat. 7 (Class F)
- Specification plug: Cat. 6A (Class EA)
- Backwards compatible versions: Cat. 6A, Cat. 6 and below
- Suitable for:
- PoE IEEE 802.3af Class 1 / PD Type 1 / 2 pairs,
- PoE IEEE 802.3af Class 2 / PD Type 1 / 2 pairs,
- PoE IEEE 802.3af Class 3 / PD Type 1 / 2 pairs,
- PoE+ IEEE 802.3at Class 4 / PD Type 2 / 2 pairs;

- Shielding class: S/FTP
- Shielding 1: foil laminated PIMF (100% density)
- Shielding 2: braid
- Core material: copper
- Wire type: stranded / flexible (stranded)
- Number of cores: 8 (4 x 2 twisted pair)
- Plug: moulded, shielded
- Contact surface: Pins gold-plated



③	MOLDED	PVC
②	CONNECTOR	RJ45 8P8C, Nickel Plating Of Shell, Pin Gold-Plated Fu"
①	CABLE	S/FTP CAT7 26AWG(19/0.09±0.008)BC*4P+AL-FOIL+B(80*0.12AL-MG), PREMIUM PUR JACKET OD:6.0+/-0.2MM

NO PART NAME PICTURES AND COLORS CAN DIFFER FROM THE PRODUCT

FLEXLINE

DESCRIPTION

RJ45 PATCHCABLE, CAT. 7 S/FTP, PUR, BLACK

SIZE	A4	DATE	14.12.2023	CHECKED		TOL	31-39205
UNIT	MM	DRAWN	Stecher	APPROVED			
CUSTOM TARIF NO.: 85444210000							