

LANCOM 750-5G

The versatile 5G-network extension



Conveniently expand your network infrastructure with fast 5G cellular radio. The device is ideally suited for use as a modem or "external 5G antenna" and for use as mobile primary access or for backup purposes. The LANCOM 750-5G can also be easily integrated into the network as a router and, thanks to Power over Ethernet, can also be supplied with power without an additional power supply unit. Thus, the device can be flexibly placed in locations with best 5G coverage.

- Integrated 5G modem for low latency and high bandwidth for real-time applications
- VRRP support ("external 5G antenna")
- Professional backup function in combination with a LANCOM router
- Easily connects to a LANCOM router or PoE switch
- Integration into the LANCOM Management Cloud
- Powered by PoE or power supply unit
- Also operates as a stand-alone 5G router
- Maximum future compatibility, reliability, and security "Engineered in Germany"



LCOS 10.80

LANCOM 750-5G

Flexible WAN network extension

With an integrated cellular modem that supports 5G technology, the LANCOM 750-5G makes wireless broadband connectivity that enables low latency and high-performance use in real-time applications. In addition, it is ideally suited for intelligent backup scenarios.

VRRP support

By supporting VRRP, the LANCOM 750-5G provides high-speed cellular connectivity to other network gateways as an "external 5G antenna".

Gigabit Ethernet with PoE

The LANCOM 750-5G features a PoE-enabled Gigabit Ethernet port. This makes it quick and easy to integrate into the network and the device can be freely positioned wherever the 5G signal is strongest.

Integration into the LANCOM Management Cloud

The LANCOM 750-5G is effortlessly managed and monitored by the LANCOM Management Cloud. The LANCOM Management Cloud is the world's first management system for the intelligent organization, optimization, and control of your entire network. This radically simplifies the management of installations, from small to very large scenarios.

Maximum future-proofing and digital sovereignty

As an established German manufacturer of IT network solutions, LANCOM stands for reliability and know-how. Software and hardware development as well as production take place primarily in Germany, as does the hosting of the network management. Special attention is given to providing trusted solutions with outstanding security features. Another important security characteristic of the products is that they are free from backdoors, as awarded by the German Federal Ministry of Economy with the quality seal "IT Security made in Germany". All devices are always equipped with hardware that is dimensioned for the future. Even across product generations, updates to the LANCOM operating system family LCOS are available several times a year, free of charge. This guarantees a long service life while staying technically up to date, which represents a true protection of your investment. In addition, LANCOM infrastructures are easily scalable thanks to maximum compatibility.



LCOS 10.80

LANCOM 750-5G

Layer 2 features

VLAN	4.096 IDs based on IEEE 802.1q, dynamic assignment
------	--

Multicast	IGMP-Snooping, MLD-Snooping
-----------	-----------------------------

Layer 3 features

Firewall	Stateful inspection firewall including packet filtering, extended port forwarding, N:N IP address mapping, packet tagging, support for DNS targets, user-defined rules and notifications
----------	--

Quality of Service	Traffic shaping, bandwidth reservation, DiffServ/TOS, packet size control, layer-2-in-layer-3 tagging
--------------------	---

Security	Intrusion Prevention, IP spoofing, access control lists, Denial of Service protection, detailed settings for handling reassembly, session-recovery, PING, stealth mode and AUTH port, URL blocker, password protection, programmable reset button
----------	---

PPP authentication mechanisms	PAP, CHAP, MS-CHAP, and MS-CHAPv2
-------------------------------	-----------------------------------

High availability / redundancy	VRRP (Virtual Router Redundancy Protocol), analog/GSM modem backup
--------------------------------	--

Router	IPv4-, IPv6-, NetBIOS/IP multiprotokoll router, IPv4/IPv6 dual stack
--------	--

Router virtualization	ARF (Advanced Routing and Forwarding) up to separate processing of 2 contexts
-----------------------	---

IPv4 services	HTTP and HTTPS server for configuration by web interface, DNS client, DNS server, DNS relay, DNS proxy, dynamic DNS client, DHCP client, DHCP relay and DHCP server including autodetection, NetBIOS/IP proxy, NTP client, SNTP server, policy-based routing, Bonjour-Proxy, RADIUS
---------------	---

IPv6 services	HTTP and HTTPS server for configuration by web interface, DHCPv6 client, DHCPv6 server, DHCPv6 relay, DNS client, DNS server, dynamic DNS client, NTP client, SNTP server, Bonjour-Proxy, RADIUS
---------------	--

Dynamic routing protocols	RIPv2
---------------------------	-------

IPv4 protocols	DNS, HTTP, HTTPS, ICMP, NTP/SNTP, NetBIOS, PPPoE (server), RADIUS, RADSEC (secure RADIUS), RTP, SNMPv1,v2c,v3, TFTP, TACACS+, IGMPv3
----------------	--

IPv6 protocols	NDP, stateless address autoconfiguration (SLAAC), stateful address autoconfiguration (DHCPv6), router advertisements, ICMPv6, DHCPv6, DNS, HTTP, HTTPS, PPPoE, RADIUS, SMTP, NTP, Syslog, SNMPv1,v2c,v3, MLDv2, NPTv6 (NAT66)
----------------	---

Tunneling protocols (IPv4/IPv6)	6to4, 6in4, 6rd (static and over DHCP), Dual Stack Lite (IPv4-in-IPv6-Tunnel), 464XLAT
---------------------------------	--

Security

Intrusion Prevention	Monitoring and blocking of login attempts and port scans
----------------------	--

IP spoofing	Source IP address check on all interfaces: only IP addresses belonging to the defined IP networks are allowed
-------------	---

Access control lists	Filtering of IP or MAC addresses and preset protocols for configuration access
----------------------	--

Denial of Service protection	Protection from fragmentation errors and SYN flooding
------------------------------	---



LANCOM 750-5G

Security

General	Detailed settings for handling reassembly, PING, stealth mode and AUTH port
Password protection	Password-protected configuration access can be set for each interface
Alerts	Alerts via e-mail, SNMP traps and SYSLOG
Authentication mechanisms	EAP-TLS, EAP-TTLS, PEAP, MS-CHAP, MS-CHAPv2 as EAP authentication mechanisms, PAP, CHAP, MS-CHAP and MS-CHAPv2 as PPP authentication mechanisms
Adjustable reset button	Adjustable reset button for 'ignore', 'boot-only' and 'reset-or-boot'

High availability / redundancy

VRRP	VRRP (Virtual Router Redundancy Protocol) for backup in case of failure of a device or remote station.
FirmSafe	For completely safe software upgrades thanks to two stored firmware versions, incl. test mode for firmware updates

Performance

Routing-Performance	Data regarding the overall routing performance can be found inside the LANCOM tech paper "Routing-Performance" on www.lancom-systems.com
---------------------	--

Cellular radio

Supported standards	5G, LTE, UMTS and HSPA support (mode of transmission automatically or manually adjustable), 2G/GSM is not supported
Supported 5G modes	5G standalone (SA), 5G non-standalone (NSA)
Supported mobile bands (5G)	n1 (2100 MHz), n2 (1900 MHz), n3 (1800 MHz), n5 (850 MHz), n7 (2600 MHz), n8 (900 MHz), n12 (700 MHz), n13 (700 MHz), n14 (700 MHz), n18 (850 MHz), n20 (800 MHz), n25 (1900 MHz), n26 (850 MHz), n28 (700 MHz), n29 (700 MHz), n30 (2300 MHz), n38 (2600 MHz), n40 (2300 MHz), n41 (2500 MHz), n48 (3500 MHz), n66 (2100 MHz), n70 (2000 MHz), n71 (600 MHz), n75 (1500 MHz), n76 (1500 MHz), n77 (3700 MHz), n78 (3500 MHz), n79 (4700 MHz)
Supported mobile bands (4G)	B1 (2100 MHz), B2 (1900 MHz), B3 (1800 MHz), B4 (1700 MHz), B5 (850 MHz), B7 (2600 MHz), B8 (900 MHz), B12 (700 MHz), B13 (700 MHz), B14 (700 MHz), B17 (700 MHz), B18 (850 MHz), B19 (850 MHz), B20 (800 MHz), B25 (1900 MHz), B26 (850 MHz), B28 (700 MHz), B29 (700 MHz), B30 (2300 MHz), B32 (1500 MHz), B34 (2000 MHz), B38 (2600 MHz), B39 (1900 MHz), B40 (2300 MHz), B41 (2500 MHz), B42 (3500 MHz), B43 (3700 MHz), B48 (3500 MHz), B66 (1700 MHz), B71 (600 MHz)
Supported mobile bands (3G)	Band 1 (2100 MHz), Band 2 (1900 MHz), Band 4 (1700 MHz), Band 5 (850 MHz), Band 8 (900 MHz), Band 19 (800 MHz)
Diversity support	Receive diversity on the aux antenna (3G); MIMO (4x4) for LTE (4G); MIMO (4x4) for 5G
Supported SIM card formats	Micro-SIM (3FF), Nano-SIM (4FF) via adaptor



LCOS 10.80

LANCOM 750-5G

Interfaces

ETH1 (PoE)	10/100/1000 Base-T, autosensing, auto node hub, PoE compliant with IEEE 802.3af. The port supports energy saving according to IEEE 802.3az
Serial interface	Serial configuration interface / COM port (USB-C): 9,600 - 115,000 baud.
External antenna connectors	Four SMA antenna connectors for external 5G antennas

Management and monitoring

Management	LANCOM Management Cloud, LANconfig, WEBconfig, LANCOM Layer 2 management (emergency management)
Management functions	Alternative boot configuration, voluntary automatic updates for LCMS and LCOS, individual access and function rights up to 16 administrators, RADIUS and RADSEC user management, remote access (WAN or (W)LAN, access rights (read/write) adjustable separately), SSL, SSH, HTTPS, Telnet, TFTP, SNMP, HTTP, access rights via TACACS+, scripting, timed control of all parameters and actions through cron job
FirmSafe	Two stored firmware versions, incl. test mode for firmware updates
automatic firmware update	configurable automatic checking and installation of firmware updates
Monitoring	LANCOM Management Cloud, LANmonitor, WLANmonitor
Monitoring functions	Device SYSLOG, SNMPv1,v2c,v3 incl. SNMP-TRAPS, extensive LOG and TRACE options, PING and TRACEROUTE for checking connections, internal logging buffer for firewall events
Monitoring statistics	Extensive Ethernet, IP and DNS statistics; SYSLOG error counter, accounting information exportable via LANmonitor and SYSLOG
IPerf	IPerf is a tool for measurements of the bandwidth on IP networks (integrated client and server)
SLA-Monitor (ICMP)	Performance monitoring of connections
Netflow	Export of information about incoming and outgoing IP traffic

Hardware

Power supply	Via Power over Ethernet, compliant with IEEE 802.3af
Environment	Temperature range 0–40°C; humidity 0–95%; non-condensing
Housing	Robust synthetic housing with aluminum body, rear connectors, ready for wall mounting, Kensington lock; 205 x 42 x 205 mm (W x H x D)
Fans	None; fanless design without rotating parts, high MTBF
Power consumption (Idle)	Approx. 4,9 W via power adapter (value refers to the power for the device and power adapter), about 6,9 W via PoE (value refers to the power for the device only)
Power consumption (max)	Approx. 10,1 W via power adapter (value refers to the overall power for the device and power adapter), about 13,0 W via PoE (value refers to the power for the device only)



LANCOM 750-5G

Declarations of conformity*

Europe/EFTA	CE
IPv6	IPv6 Ready Gold
Country of Origin	Made in Germany
*) Note	You will find all declarations of conformity on our website at www.lancom-systems.com/doc

Scope of delivery

Manual	Quick Installation Guide (DE/EN)
Cable	1 Ethernet cable, 3 m
Antennas	Four 2 dBi 5G/LTE/UMTS-antennas
Power supply unit	External power adapter (230 V), NEST 12 V/2.5 A DC/S, coaxial power connector 2.1/5.5 mm, temperature range from 0 to +40° C, LANCOM item no. 111884 (EU)

Support

Warranty extension	Free warranty extension up to 3 years (replacement service for defects) For details, please refer to the service and support conditions at www.lancom-systems.com/support-conditions or at www.lancom.de/rma .
Security updates	Up to 2 years after End of Sale of the device (but min. 3 years, see www.lancom-systems.com/product-tables), can be extended by purchasing LANcare products
Software updates	Regular free updates including new features as part of the LANCOM Lifecycle Management (www.lancom-systems.com/lifecycle)
Manufacturer support	For LANcommunity partners up to the End of Life of the device For end customers with LANcare Direct or LANcare Premium Support during the LANcare validity
LANcare Basic S	Security updates until EOL (min. 5 years) and 5 years replacement service with shipment of the replacement device within 5 days after arrival of the defective device (8/5/5Days), item no. 10720
LANcare Advanced S	Security updates until EOL (min. 5 years) and 5 years NBD advance replacement with delivery of the replacement device within one business day (8/5/NBD), item no. 10730
LANcare Direct Advanced 24/7 S	Direct, prioritized 10/5 manufacturer support incl. 24/7 emergency hotline and security updates for the device, NBD advance replacement with delivery of the device on the next business day (24/7/NBD), guaranteed first response times (SLA) of max. 30 minutes for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10776, 10777 or 10778)
LANcare Direct 24/7 S	Direct, prioritized 10/5 manufacturer support incl. 24/7 emergency hotline and security updates for the device, guaranteed first response times (SLA) of max. 30 minutes for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10752, 10753 or 10754)



LCOS 10.80

LANCOM 750-5G

Support

LANcare Direct Advanced 10/5 S	Direct, prioritized 10/5 manufacturer support and security updates for the device, NBD advance replacement with delivery of the device on the next business day (10/5/NBD), guaranteed first response times (SLA) of max. 2 hours for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years.(item no. 10764, 10765 or 10766)
--------------------------------	--

LANcare Direct 10/5 S	Direct, prioritized 10/5 manufacturer support and security updates for the device, guaranteed first response times (SLA) of max. 2 hours for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years.(item no. 10740, 10741 or 10742)
-----------------------	---

Software

Lifecycle Management	After discontinuation (End of Sale), the device is subject to the LANCOM Lifecycle Management. Details can be found at: www.lancom-systems.com/lifecycle
----------------------	---

Anti-backdoor policy	Products from LANCOM are free of hidden access paths (backdoors) and other undesirable features for introducing, extracting or manipulating data. The trust seal "IT Security made in Germany" (ITSMIG) and certification by the German Federal Office for Information Security (BSI) confirm the trustworthiness and the outstanding level of security.
----------------------	--

LANCOM Management Cloud

LANCOM LMC-A-1Y LMC License	LANCOM LMC-A-1Y License (1 Year), enables the management of one category A device for one year via the LANCOM Management Cloud, item no. 50100
LANCOM LMC-A-3Y LMC License	LANCOM LMC-A-3Y License (3 Years), enables the management of one category A device for three years via the LANCOM Management Cloud, item no. 50101
LANCOM LMC-A-5Y LMC License	LANCOM LMC-A-5Y License (5 Years), enables the management of one category A device for five years via the LANCOM Management Cloud, item no. 50102

Accessories

External antenna	AirLancer O-360Q-5G, omnidirectional outdoor antenna MIMO (4x4), for all 4G/5G bands (700-3800 MHz), item no. 61234
LANCOM Wall Mount LN	Robust mounting plate for simple, theft-proof mounting of LANCOM devices with LN housing, Item no. 61342

Item number(s)

LANCOM 750-5G (EU)	61707
--------------------	-------

LANCOM Systems GmbH
A Rohde & Schwarz Company
Adenauerstr. 20/B2
52146 Wuerselen | Germany
info@lancom.de | www.lancom-systems.com

LANCOM, LANCOM Systems, LCOS, LANcommunity and Hyper Integration are registered trademarks. All other names or descriptions used may be trademarks or registered trademarks of their owners. This document contains statements relating to future products and their attributes. LANCOM Systems reserves the right to change these without notice. No liability for technical errors and/or omissions. 11/24