

Datasheet



Camera

BC510

Synology

BC510



AI-Powered Camera for Securing Any Location

The BC510 is a versatile IP66 and IP67-rated 5 MP wide-angle AI camera suitable for both indoor and outdoor use. Boasting a high resolution of 2880×1620 at 30 FPS, a 110° horizontal wide angle view, and night vision capability, the BC510 captures all the details you need. Plus, it features edge AI capabilities for enhanced security and response efficiency.

- **Crisp Video, Night and Day**
5 MP sensor with wide-angle lens, recording at 30 FPS, and high-power IR LED for 30 meters of night vision
- **IP66 & IP67 Weather-resistant**
Fully dust-proof and resistant to low-pressure water jets
- **Edge AI Detection**
Camera-based AI capabilities for enhanced security
- **Failover Edge Recording**
Supports failover recording onto microSD card, in case of network failure
- **Security and Compliance**
Suitable for sensitive applications thanks to US NDAA & TAA compliance

Consistent clear footage, 24/7

Highly detailed, wide-angle coverage helps secure large areas, day or night.

- High resolution of 5 MP (2880×1620) 16:9 provides clear and detailed videos
- 110° wide horizontal viewing angle captures large areas at once and reduces the need for multiple cameras
- Large aperture of F1.8 and multi-exposure HDR provide good low-light performance without overexposing lighter areas
- High power infrared LED provides clear night vision up to 30 meters

Flexible deployment options

A multi-platform design enables flexible deployment options to best fit your surveillance needs.

- **Surveillance Station:** Host video locally on your NAS for complete local control¹
- **BeeStation Plus:** Build your own private monitoring hub and manage cameras through the [BeeCamera app](#)
- **Third-Party System:** Connect to other NVR or VMS using the standard ONVIF protocol

Secure and safe, always reliable

From monitoring to recording, protect your footage with our integrated safeguards.

- The camera is NDAA and TAA compliant, meeting US government procurement regulations
- Privacy masks can be permanently embedded into footage or applied to live view to cover sensitive areas
- Long-term firmware support from Synology includes security patches and updates

Notes:

1. When used with Surveillance Station, the camera must be paired with a Surveillance Device License Pack. Please ensure sufficient licenses are available.

Hardware Overview



No.	Name	No.	Name
1.	Microphone	3.	MicroSD Slot
2.	Status Indicator	4.	Reset Button

Technical Specifications

Optical

Image Sensor	1/2.7"
IR LED wavelength	850 nm
Max. IR distance	30m (98.4ft) (0.001lux)
Shutter Speed	1/16000 s to 1/30 s
Day & Night	Automatically removable infrared-cut filter

Lens

Lens type	Fixed Focal
Focal Length	2.8 mm
DORI	D: 60m, O: 24m, R: 12m, I: 6m
Aperture	F1.8

Video

Max. video resolution	2880×1620 @ 30 FPS
Multi-exposure HDR	v
DNR	• 3DNR • 2DNR

Audio

Microphone	v
------------	---

I/O

Ethernet	RJ45 10M/100M Ethernet port X 1
Reset	v
On-Board Storage	MicroSD card slot X 1 Supported file format: exFAT Note: microSD card is not included

Power Supply

IEEE 802.3af Type 1 Class 3 or 12V DC

Note	- Compatible DC power adapter: 12V/1A (Ø2.1mm) - The product does not include a PoE switch or a 12V DC power adapter. Please purchase separately.
------	---

General

Form Factor	Bullet
Dimension	Ø110 × 161 mm (Ø4.33 × 6.34")
Weight	353 g (0.78 lbs)

Temperature

Operating Condition	Starting temperature: -30°C to 50°C (-22°F to 122°F) Operating temperature: -30°C to 50°C (-22°F to 122°F) (IR off) Operating temperature: -30°C to 40 °C (-22°F to 104°F) (IR on) Operating humidity: 5%~95% (non-condensing)
Storage Condition	Storage temperature: -40°C to 60°C (-40°F to 140°F) Storage humidity: 5%~95% (non-condensing)

Certification

Regulatory Compliance	FCC, CB, IC, CE, UKCA, BSMI, VCCI, RCM, KC, JATE
Environment	REACH, ROHS, WEE
Waterproof	• IP66 • IP67
Vandal	-
NDAA Compliant	v
TAA Compliant	v

Warranty

3-year

Packaging Content

- Main Unit X 1
- Installation guide X 1
- Screw pack X 1
- RJ45 cap cover X 1

Software Specifications

Video & Audio	
Main Stream	2880×1620 @ 30 FPS 2560×1440 @ 30 FPS 2304×1296 @ 30 FPS 1920×1080 @ 30 FPS
Maximum Bitrate	8192 kbps
Sub Stream	1280×720 @ 30 FPS
Video Format	• H.264 • H.265
Bitrate Control	• Maximum bitrate • Variable bitrate
Audio Compression	G.711
Audio Denoise	v
Image Adjustment	• Brightness • Contrast • Sharpness • Saturation • White Balance • Exposure Control • High Dynamic Range (HDR) • 3D/2D Noise Reduction • 50/60 Hz Flicker Reduction • Day/Night mode • Overlay
Day/Night Mode	• Auto • Day • Night • Schedule
Video Orientation	• Mirror • Flip • Rotation (0°, 90°, 180°, 270°)

Privacy Mask	• Removeable/Unremovable mode • Up to 5 zones
Max RTSP Connections	4

Analytics

Event Analytics	• Audio Detection • Tampering Detection • Motion Detection
People & Vehicle	• People Detection • Vehicle Detection • Crowd Detection • Loitering Detection
Counting	People and Vehicle Counting
Intrusion	One way or Two way
Instant Search	• Motion • Vehicle • People
Auto Tracking	People

Security

IP Filter	• Auto Block • Allow/Block list
Connection Management	v
Firmware Update	• Automatically update to the important version • Automatically update to the latest version • Manual upload
Signed Firmware	v
HTTPS	v
SRTP	v

Storage Management

Storage	microSD Card & Synology NAS
SD Card Recording Mode	• Event Analytics • Disconnected with NAS

Camera Web Interface

Liveview	v
Network	• Auto Block • Allow/Block list • Connection Management • Fixed IP/DHCP
System	• Reset • Restart • Manual Firmware Upgrade • DST • Time Zone
Camera Log Export	v
Protocol Support	HTTP, HTTPS, TLS v1.2, TCP/IP, UDP, IPv4, UPnP, RTSP, NTP, DHCP, SSL, RTP, SRTP
Supported Browsers	Google Chrome
Supported Language	English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svenska, Nederlands, Русский, Polski, Magyar, Português do Brasil, Português Europeu, Türkçe, Český, ภาษาไทย, 日本語, 한국어, 繁體中文, 简体中文

SYNOLOGY INC. © 2026, Synology Inc. All rights reserved. Synology, the Synology logo are trademarks or registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product descriptions at anytime, without notice.