

# ClickShare C-10

Making presentation flow in medium-sized and large meeting rooms



- Full BYOD support
- Seamless content sharing with Button or Desktop App
- Enhanced security, connected and cloud managed
- Full interactivity with touch back, blackboarding, annotation
- Delivered with 1 Button

Technology can help to make meeting participants engaged, inspired and active. ClickShare C-10 adds interactive features to full BYOD, easy wireless presentation in any medium to large meeting room. It is the wireless presentation hub that makes your meetings flow with one click in the ClickShare Button or ClickShare App, from any laptop or mobile device.

Find out what's new in the latest ClickShare update

## Full BYOD content sharing

With the ClickShare C-10, you can start a meeting and get your content on screen within seconds. No matter the device you are using. Plug & Play with the ClickShare Button, that works perfectly on both pc or Mac. Go for workflow integration with the ClickShare App on laptop, mobile or tablet. Or enable full Bring Your Own Device (BYOD) on a 4K canvas: screen mirroring with Airplay, GoogleCast and Miracast works flawlessly.

Anyone, including guests, can share content wirelessly to the central room display with our one-click meeting experience. Two users can share side by side in full HD on screen. No cables, no software to download, no training needed.

## Enjoy interactive, creative meetings

ClickShare C-10 users can benefit from advanced interactive features including local view of the room display, decide what they share (either a full screen or a single window), annotation, blackboarding and touch back support that allows users to control the touchscreen in the room. Designed especially to make meetings richer and more dynamic. C-10 makes hybrid collaboration flow in creative meetings, brainstorming and discussion in one click.



### Enhanced security and seamless integration

Designed for enterprise rollouts, the IT-grade C-10 offers you enhanced security features (ISO27001 certified) and a wide range of connectivity options. With the XMS Cloud Management Platform you enjoy remote management of units and clear analytics to drive your digital workplace. For practical questions on network deployment of the ClickShare range, check our technical support or get in touch with your Barco contact.

### Boost collaboration in your meeting room

The ClickShare C-10 can be used stand-alone or in combination with your existing conference room. It empowers meetings with simple, one-click wireless content sharing. ClickShare completes the room set-up and makes presentation simple, easy and wireless. Designed to fit your business perfectly and evolve with it. With flexibility for the future built in, it's one of the smartest investments you can make in your meeting room.

## PRODUCT SPECIFICATIONS

## CLICKSHARE C-10

| General specifications                                               |                                                                                                                                                      |
|----------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating system                                                     | Windows 8/8.1/10/11 macOS 10.13 and higher.<br>Android v9 and higher (ClickShare App)*<br>iOS 12 and higher (ClickShare App)*                        |
| Video outputs                                                        | 4K UHD (3840*2160) @ 30Hz. HDMI 1.4b                                                                                                                 |
| Audio output                                                         | HDMI                                                                                                                                                 |
| USB                                                                  | 1 X USB-A, 1 X USB-C                                                                                                                                 |
| ClickShare Buttons                                                   | 1                                                                                                                                                    |
| ClickShare App                                                       | Desktop & Mobile                                                                                                                                     |
| Native protocols                                                     | Airplay, Google Cast, Miracast*                                                                                                                      |
| Maximum number of simultaneous connections (with Buttons and/or App) | 32                                                                                                                                                   |
| Noise Level                                                          | Max. 25dBA @ 0-30°C<br>Max. 30dBA @ 30-40°C                                                                                                          |
| Authentication protocol                                              | WPA2-PSK in stand alone mode<br>WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode                                      |
| Wireless transmission protocol                                       | IEEE 802.11 a/g/n/ac and IEEE 802.15.1                                                                                                               |
| Reach                                                                | Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit<br>Frequency band 2.4 GHz and 5 GHz |
| Frequency band                                                       | 2.4 GHz and 5 GHz (DFS channels supported in select number of countries)                                                                             |
| Connections                                                          | 1x Ethernet LAN 1Gbit<br>1x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front)                                                                        |
| Temperature range                                                    | Operating: 0°C to +40°C (+32°F to +104°F)<br>Max: 35°C (95°F) at 3000m<br>Storage: -20°C to +60°C (-4°F to +140°F)                                   |
| Humidity                                                             | Storage: 0 to 90% relative humidity, non-condensing<br>Operation: 0 to 85% relative humidity, non-condensing                                         |
| Anti-theft system                                                    | Kensington lock                                                                                                                                      |
| Certifications                                                       | FCC/CE                                                                                                                                               |
| Touch screen support & Interactivity                                 | Yes                                                                                                                                                  |
| Room Dock (peripheral support)                                       | No                                                                                                                                                   |
| Local view                                                           | Yes                                                                                                                                                  |
| Network connection                                                   | LAN & WiFi                                                                                                                                           |
| Management and reporting                                             | Yes                                                                                                                                                  |
| Warranty                                                             | 1 year standard. 5 years coverage via SmartCare                                                                                                      |
| *                                                                    | * depends on configuration, available in future firmware updates                                                                                     |
| ClickShare Base Unit dimensions                                      |                                                                                                                                                      |
| Dimensions (HxWxD)                                                   | 34 mm x 135 mm x 135 mm                                                                                                                              |
| Power supply                                                         | Standard 110/220 V AC plug                                                                                                                           |
| Power consumption                                                    | Operational: 5-10W, 24W Max                                                                                                                          |
| Weight                                                               | 900 gr                                                                                                                                               |

Last updated: 02 Feb 2022

Technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest information.