


ACT Connectivity Solutions – Koolhovenstraat 1E – 3772MT – Barneveld – The Netherlands



ITEM	PART	DESCRIPTION
P1	USB-C male	PCB + Connector +10nF capacitor
P2	USB-C male	PCB + Connector +10nF capacitor + EMARK
P1 + P2	Connector type	USB-C male
	Contacts	Nickel plated
	Hood	Black plastic
	E-marker	Yes
Cable	Shielding	Copper foil + Mylar Braid
	Cable colour	Black
	Outer jacket	TPE
	Wire gauge	28 AWG
	Outer diameter	Ø5.5 mm
	Bend radius	55mm
	Conductive Resistance	3 ohms MAX
	Insulation Resistance	10M ohm MIN.
	EPR	up to 240W
	Max. bandwidth	80Gbps
	Max. PD	240W
	Max. resolution @ 30Hz	15360 x 8640 (16K)

Item No.	Length	Max. PD
AC7452	1,5m	240W

Additional information	
USB	1.1, 2.0, 3.0, 3.1, 3.2, 4, 4 v2.0
Bandwidth	up to 80Gbps
PD	5, 9, 12, 15, 20V, 24V, 36, 48V up to 5A
DP-Alt mode	Yes
Max. Resolution	15360 x 8640 (16K)
Thunderbolt support	Thunderbolt 3/4/5



USB4 v2.0 80Gbps cable, USB-C male -USB-C male 240W USB-IF certified

Revision : 01

Date : 20-10-2025

Drawn by : MR

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.

