

LogiLink®



HDMI Extender Set via Network Cable

4K/60 Hz, Extend up to 70 m

Art. No.: HD0063

Allows you to extend HDMI video/audio signals by up to 70 m over a networking cable; with resolution up to 4K/60 Hz. Also, it works to extend IR signals from remote controls of the video source.


Features:

- » Supports 4K@60 Hz up to 70 m over a single Cat. 5e/6/7/8 cable
- » Bandwidth: 6 Gbps/600 MHz per channel (18 Gbps total)
- » Supports 12 bit per channel (36 bit all channels) deep color
- » Compatible with HDCP 1.4/2.2 and supports Full 3D, DDC, HDR10
- » Features IR return which enables you to control the video source from your video destination
- » Supports bi-directional PoC (Power over Cable)
- » Supports uncompressed audio such as LPCM 7.1
- » Supports compressed audio such as DTS, Dolby Digital

TX:



RX:



- (a) Connect to DC 12 V power supply
- (b) HDMI In: Connect to HDMI source device
- (c) IR Out: IR signal output port
- (d) Short click to Reset
- (e) Ethernet Ports: Connects transmitter (TX) to receiver (RX) via network cable
- (f) Link LED Indicator
- (g) HDMI Out: Connect to HDMI display device
- (h) IR In: IR signal input port




*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



HD0063



Made in China



Specifications:

Transmitter (TX) Interface	1x RJ45 jack, 1x HDMI-A female, 1x DC power jack, 1x IR TX
Receiver (RX) Interface	1x RJ45 jack, 1x HDMI-A female, 1x DC power jack, 1x IR RX
HDMI Version	2.0b
HDCP Version	1.4/2.2
Working Distance	Up to 70 m
Output Resolution	480i@60 Hz, 576i@50 Hz, 1080i@50/60 Hz, 480p@60 Hz, 576p@50Hz, 720p@50/60 Hz, 1080p@24/25/30/50/60 Hz, 4K@24/25/30/50/60 Hz
Video Bandwidth	6 Gbps/600 MHz (18 Gbps total)
Deep Color	12 bit
IR Support	Yes
3D Support	Yes
POC (Power Over Cable)	Yes, DC 12 V
DDC (Display Data Channel)	Yes
HDR (High-Dynamic Range)	HDR10
Chassis Material	Metal
Power Consumption	TX: 1.3 W, RX: 1.6 W
Power Supply	12 V/1 A (12 W)
Uncompressed Audio	LPCM 7.1
Compressed Audio	DTS, Dolby Digital
Networking Cable	Cat.5e/6/7/8
Compressed Audio	DTS, Dolby Digital
Operating Temperature	0–50°C
Operating Humidity	10–85% RH (no condensation)
Dimensions	TX/RX: 8.4 x 7.65 x 2 cm
Weight	TX: 120 g; RX: 190 g



*The specifications and pictures are subject to change without prior notice.
 *All trade names referenced are the registered trademarks of their respective owners.



Specification of External Power Supply:

Input Voltage	100–240 V, 50/60 Hz 0.4 A max.
Output Power	12 V/1 A, 12 W
DC Plug	5.5 x 2.1 mm
Dimensions	74.4 x 54.9 x 39.9 mm
Cable Length	1.2 m
Weight	0.1 kg



Package Contents:

- » 1x HDMI Extender Set
- » 1x IR TX Cable
- » 1x IR RX Cable
- » 1x Power Adapter 12 V/1 A
- » 1x User Manual

Package Information:

- » Packing Dimension: 246 x 195 x 60 mm
- » Packing Weight: 0.571 kg
- » Carton Dimension: 505 x 235 x 340 mm
- » Carton Q'ty: 10 pcs
- » Carton Weight: 6.2 kg



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

