


HT 221 PPB

54,6 cm / 21.5" Diagonal
LED Backlight – Format 16:9

- 21,5" Touch Monitor LED Backlight
- 1920 x1080 Full HD Resolution
- 10-Point Touch P-Cap Technology
- 178° / 178° Ultra Wide Viewing Angle
- Triple Input: DP + HDMI + VGA
- Built-In Stereo Speakers
- IP65 Rating Level
- Display Protection: Thickness 3mm
- Multi-Video Modes
- Wall-Mountable (VESA)
- Edge to Edge Glass without raised frame



54,6 cm / 21.5"

The monitor stand is not included. A VESA compatible stand can be purchased separately for desktop usage.

Part. No.: HT 221 PPB

SIZE, RESOLUTION



21.5"
16:9 Aspect Ratio



Full HD
1920 x 1080

CONNECTIVITY, SPEAKER



VGA
HDMI
DP



Built-In
Stereo Speaker

VIEWING ANGLE, VESA



178° Wide
Viewing Angle



VESA
Wall-Mountable

OTHER FEATURES



10
Point
Touch



Panel
Brightness





IP65



≥ 6H
Hardness

Display Size	54,6cm / 21.5" Diagonal
Panel Type	TFT – LED Backlight, VA Panel *
Aspect Ratio	16:9
Resolution (H x V)	1920 x 1080 Full HD
Brightness	350 cd/m ² (Panel) – 300 cd/m ² (Monitor)
Contrast (Typ.)	1.000:1 (Typical)
Contrast (Active)	5.000.000:1 (Active)
Viewing Angle L/R; U/D	178° H – 178° V (CR > 10)
Response Time	4 msec
Pixel Pitch	0,248 (H) x 0,248 (V) mm
Touch Type	Projected Capacitive Type – 10 Point Touch Cover Glass + LOCA + ITO Glass
Display Colors	16.7M Colors
Horizontal Frequency	30 ~ 83 kHz
Vertical Frequency	56 ~ 75 Hz
Max Display Frequency	1920 x 1080 @ 60Hz
Input 1	D-Sub (VGA)
Input 2	HDMI
Input 3	Display Port
Input 4	USB 3.0 x 1 (for touch)
Buil-in Speakers	Yes, 2W x 2; Earphone Jack
Power Consumption	On: 13W; Stand-by: 0,37W; Off: 0,2W
AC Power Range	AC 100 ~ 240 Volt; 50 ~ 65 Hz
Product Dimensions	510,9 x 49,1 x 313 mm (W x D x H)
Packing Dimensions	563 x 101 x 428 mm (W x D x H)
Net / Gross Weight	4,14 Kg / 5,34 Kg (± 0,3Kg)
Bezel & Color Plan	Front TP: Black Color; Bezel, Back Cover: Black Color



VESA Mounting	100 x 100 mm
Monitor Stand	Not included. A VESA compatible stand can be purchased separately for desktop usage.
Tilt / Kensington Lock	- / Yes
Display Protection	Thickness 3 mm
Hardness / Transmittance	≥6H Toughened hard panel surface / ≥85%
IP Rating Level	IP 65 ** (Front), Water and Dust Protection
Controls	Menü, (+), (-), AUTO, Power
Color	9300, 6500, 5500, User Mode
Preset Mode	PC, Movie, Game, ECO Modes
On Screen Display	11 OSD Languages
Accessory	Power Cable (1,5m); HDMI Cable (1,5m); USB 2.0 (B-A) Cable (1,8m); Warranty Card; Quick Start Guide

Supplier's Name	HT221PPB
Model Name	D
Energy efficiency class for standard Dynamic Range (SDR)	13 kWh/1000h
Annual Energy Power Consumption (kWh/1000h)	13 W
On mode power demand for Standard Dynamic Range (SDR)	0,2 W
Off mode power demand (W)	0,4 W
Standby mode power demand (W)	54,6cm / 21,5"
Screen Diagonal (cm / inches)	1920 x 1080
Resolution	HT221PPB

PART. NO.:
HT 221 PPB



4 711404 023347 >