

LH351ST

Compact high brightness Short throw Full HD 4LED projector



- **Bright 3300 lumens for lights on viewing - Full HD 1080p 4LED short throw projector**
- **Compact and short throw lens for easy installation - 360-degree and portrait projection**
- **Optoma Management Suite (OMSC)[™] - Remotely manage and control your device with real-time monitoring, and scheduling, helping to reduce downtime, streamline operations, and cut operating costs.**
- **Optoma Smart Control App - Streamlines device management allowing you to command, control and make image corrections all from your mobile device.**



The LH351ST is one of Optoma's most compact and hassle-free Full HD short throw projectors to date. Designed for maintenance-free continuous operation, this 3300-lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor.

Compatible with Optoma Management Suite (OMSC)[™] and Optoma's latest Smart Control App, control and manage your devices remotely with ease.

Specifications

EAN: 5 055387 669635 , Colour: White



Display/image	
Display technology	DLP®
Resolution	1080p Full HD (1920x1080)
Brightness	3,300 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	85%
Screen size	0.76m ~ 7.62m (30" ~ 300") diagonal
Lamp info	
Light source type	4 LED
LASER life	30,000 hours
Optical	
Throw ratio	0.49:1
Projection distance (m)	0.306m - 3.055m
Zoom type	Fixed
Focal length (mm)	6.9
Native offset	107%
Connectivity	
Connections	Inputs 2 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232, 1 x RJ45
General	
Noise level (min)	29dB
Noise level (max)	35dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10000ft.
Speaker count	1
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA Batteries Basic user manual
Power	
Power supply	AC 100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	124W
Power consumption (max)	226W
Weight and dimensions	
Dimensions (W x D x H) mm	307 x 228 x 125
Gross weight	5 kg
Net weight	3.2 kg