

DISPLAYPORT CABLES - TAA COMPLIANT

TAA-Compliant DisplayPort™ Cable with Latches - 8K 60Hz

The C2G TAA-Compliant DisplayPort™ Cable with Latches – 8K 60Hz offers excellent video and audio performance, making it ideal for high-resolution displays and professional use. It meets the DisplayPort 1.4 standard, supporting 8K resolution at 60Hz (7680 x 4320) for clear, detailed visuals. With a data bandwidth of up to 32.4Gbps, it delivers uncompressed audio and deep color depth.

This cable is ideal for connecting a computer's DisplayPort output to a monitor with a DisplayPort input. Latching connectors ensure a secure connection, making it perfect for demanding applications.



Front



Side

ITEM	DESCRIPTION
C2G50112	3ft (0.9m) C2G TAA-Compliant DisplayPort™ Cable with Latches - 8K 60Hz
C2G50113	6ft (1.8m) C2G TAA-Compliant DisplayPort™ Cable with Latches - 8K 60Hz
C2G50114	10ft (3m) C2G TAA-Compliant DisplayPort™ Cable with Latches - 8K 60Hz

DISPLAYPORT CABLES - TAA COMPLIANT

TAA-Compliant DisplayPort™ Cable
with Latches - 8K 60Hz

FEATURES

- TAA Compliant
- Fully compliant with the DisplayPort 1.4 specification
- Supports 8K resolution at 60Hz (7680 x 4320) with Display Stream Compression (DSC), and 8K at 30Hz without DSC, delivering clear, detailed visuals
- Supports data bandwidth up to 32.4Gbps
- **Cable jacket:**
VW-1 rated, compliant with UL standards, ensuring safe and reliable performance for basic applications
- Secure connection with latches to prevent accidental disconnections
- Backed by a C2G lifetime warranty



DISPLAYPORT CABLES - TAA COMPLIANT


Specifications

		C2G50112-14
PHYSICAL SPECIFICATIONS	Minimum Bend Radius	C2G50112-13: 58mm
		C2G50114: 70mm
	Jacket Rating	VW-1
	C2G50112-13	30AWG
		OD: 5.8±0.2 mm
	C2G50114	28AWG
		OD: 7.0±0.2mm
ELECTRICAL SPECIFICATIONS	Voltage	30V
	Conductor Resistance	3 Ω Max
	Insulation Resistance	DC200V, 10MΩ Min
PHYSICAL CHARACTERISTICS	Housing	Plastic, Black
	Cable	PVC, Black
	Length	C2G50112 : 3' ± 1.19"
		C2G50113 : 6' ± 1.97"
		C2G50114 : 10' ± 1.97"
	Shell	Metal, Black
	Operation Temperature	-20°C to 80°C
	Storage Temperature	-10°C to 55°C
	Regulatory Approvals	CE marked; Conforms to 2011/65/EU ROHS 2
CONNECTORS	Connector Type 1	DisplayPort Latching Male
	Connector Type 2	DisplayPort Latching Male
SIGNAL SPECIFICATIONS	DisplayPort	1.4
	Eye Diagram	8.1G
	Data Transfer Rate	32.4Gbps
	Video Resolution	8K (7680 X 4320)
	Refresh Rate	60Hz (with DSC), 30Hz (without DSC)


DISPLAYPORT CABLES - TAA COMPLIANT

TECHNICAL DRAWINGS

C2G50112-13



C2G50114



LEGRAND | AV COMMERCIAL BRANDS

C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold

SIMPLIFIED CONNECTIVITY

USA 800.506.9607 customer-service@c2g.com

APAC +852 2145 4099 av.asia.sales@legrand.com

EMEA +31 495 580 840 c2g.emea@av.legrand.com

©2025 Legrand AV Inc. 250101 Rev A 3/25 C2G is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.