

Product datasheet

Specifications



Easy Rack PDU, Basic, Vertical, 1 Phase, 7.4kW, 230V, 32A, 21 x SCHUKO outlets, IEC60309 (32A 230VAC L+N+PE)

SEP6123G

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Number of cables	1
Provided equipment	Installation manual

Complementary

Height	56 mm
Width	56 mm
Output Voltage	230 V
Depth	1280 mm
Product weight	2.4 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Network frequency	50/60 Hz
Outlet type and quantity	21 CEE 7/3 Schuko CEE 7

Environment

Product certifications	CE
Operating altitude	0...10000 ft

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.600 cm
Package 1 Width	17.000 cm
Package 1 Length	144.000 cm
Package 1 Weight	3.393 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 064 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	34 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	18 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2 006 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	6 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	52
End of life manual availability	End of Life Information

Image of product / Alternate images

Alternative



