


133101 2 in 1 USB-C + A to RJ45 Gigabit Ethernet Cable, 1.0m

Product Images





Short Description

- Connector type: USB-C/ USB-A male to RJ45 male.
- Fast transmission rate of up to 1 Gbit/s (Gigabit Ethernet)
- Wide compatible with Multiple devices work has USB-A and USB-C port.
- Shielding for error-free data transfer
- Aluminum housing
- Plug-and-play: No drivers needed for instant use

Description

The **2-in-1 USB-C + USB-A to RJ45 Gigabit Ethernet Cable** provides a convenient and reliable solution for adding wired network connectivity to a wide range of devices. Designed with both **USB-C and USB-A connectors**, this versatile cable allows easy connection to modern laptops, tablets, and legacy computers without requiring

additional adapters.

Equipped with a **Gigabit Ethernet RJ45 port**, it delivers stable wired network speeds up to **1000 Mbps**, making it ideal for environments where reliable connectivity is essential, such as offices, home workstations, online meetings, streaming, and large file transfers. A wired connection can significantly reduce latency and improve network stability compared to wireless connections.

The compact cable design offers a **plug-and-play installation**, eliminating the need for complicated setup or external power. Simply connect the cable to your device to instantly enable high-speed Ethernet access.

Additional Information

Harmonized System (HS) code.	854442
Customs product code (TARIC).	8544421000
Angled Plug.	No
Connector 1.	USB-A, male
Connector 2.	RJ45 male
Color.	Black
EAN.	4015867244111
Model Number.	133101
Cable Length.	1m
Dimensions (W x D x H).	67 x 10 x 1000 mm
Product weight (kg).	0.032
Cable Jacket material.	PVC
Data Rate.	1Gbps
Material.	Aluminum
Chipset.	RTL8153
Standard.	● IEEE 802.3: 10Base-T (Ethernet) ● IEEE 802.3u: 100Base-TX (Fast Ethernet) ● IEEE 802.3ab: 1000Base-T (Gigabit Ethernet) ● IEEE 802.3x Flow Control (full-duplex flow control) ● IEEE 802.3az Energy Efficient Ethernet ● IEEE 802.1P layer 2 Priority Encoding and Decoding ● IEEE 802.1Q VLAN tagging and 2 VLAN ID filtering; received VLAN Tag (4 bytes) can be stripped off or preserved
Approval and Compliance.	CE, ROHS
Operating temperature.	0°C ~ 50°C
Compatible operating systems.	Windows 7/8/10/11 MacOS 10.6 or above Chrome OS Android 10 or above Linux
Package Contents.	2 in 1 USB-C + A to RJ45 Gigabit Ethernet Cable, 1.0m

