

Rack UPS, 2000 VA, black EG-UPSRACK-12

ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



Features

- Automatic output voltage regulation (AVR)
- Rack 3.4U metal case
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

Packaging

Q'ty in crtn, pcs	1
Crtn volume, CUM	0.076632
Crtn weight, kgs	25.06
Individual package size LxWxH:	525x400x225 mm
Carton size LxWxH:	620x515x240 mm
Country of origin	CN
Barcode	8716309087735
Customs code	8504408490

Package contents

UPS
Power cord
USB cable
Software CD
Spare fuse

Specifications

UPS type: line interactive, pure sine wave
Input: 220V AC $\pm$ 25%, 50Hz / 60Hz $\pm$ 10%
Output: 220V AC $\pm$ 10%, 50Hz / 60Hz $\pm$ 0.5% (on battery)
Output power factor: 0.8
Inverter output efficiency (resistive load): 85%, any load type is allowed
Switching time: no more than 10 ms (typically 6 ms)
Backup time: 8...20 mins (depends on the load)
Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 9 Ah / 2.3 kg x 3 pcs
Charge time: up to 12 hours
Sockets: input IEC C14, outputs: Schuko EU type x 1 pc, IEC C13 x 6 pcs

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Certificates

