

Temperature and Humidity Sensor – indoor

Product ref.: 150181A0



Product features

- Measuring of indoor temperature and humidity
- Regulates the room temperature in connection with one or more Homematic IP Radiator Thermostats or Homematic IP Floor Heating Actuators
- Particularly user-friendly and immediately ready for use thanks to radio communication
- Simple and flexible installation thanks to supplied adhesive strips or screws
- Integration into multi-gang frames or 55 mm frames of other manufacturers (Berker, ELSO, Gira, merten, JUNG)
- Can be used with the Home Control Access Point in connection with the Homematic IP app, the Homematic Central Control Unit CCU2 as well as with various partner solutions

Technical specifications

Supply voltage	2x 1.5 V LR03/micro/AAA
Current consumption	20 mA max.
Battery life	2 years (typ.)
Degree of protection	IP20
Ambient temperature	5 to 35 °C
Dimensions (W x H x D)	Without frame: 55 x 55 x 19 mm Incl. frame: 86 x 86 x 20 mm
Weight	85 g (including batteries)
Radio frequency	868.3 MHz/869.525 MHz
Typ. open area RF range	130 m

Logistical data

Product reference	150181A0
EAN code	4047976501816
Short description	HmIP-STH
Packing unit	90
Packing dimensions	122 x 112 x 48 mm

Package contents

Homematic IP Temperature and Humidity Sensor – indoor

Clip-on frame

Mounting plate

Double-sided adhesive strips (2x)

Screws 3.0 x 30 mm (2x) and plugs 5 mm (2x)

1.5 V LR03/micro/AAA batteries (2x)

User manual