

# ROLINE DesignSecure 625

|                    |               |
|--------------------|---------------|
| Product No.        | 19.40.1206    |
| Manufacturer       | ROLINE        |
| Manufacturer No.   | 19.40.1206    |
| EAN (single piece) | 7611990171026 |



- Compact designed UPS in futuristic design
- For Workstations and PCs
- LineInteractive UPS
- AVR (Automatic Voltage Regulation)
- Digital status display
- Integrated overvoltage protection
- Telephone/Modem connections
- USB Port for advanced Power Management Software (incl, in content of delivery)
- EMI/RFI Noise Filter
- Dimensions (HxLxW) 168 x 105 x 334 mm
- Weight: 6.3 kg
- Backup Time: up to 4 Minutes

| Technical specifications     |                          |
|------------------------------|--------------------------|
| Manufacturer                 | ROLINE                   |
| Product group                | UPS                      |
| Product type                 | UPS Line Interactive     |
| Colour                       | black /silver            |
| Scope of delivery            | UPS, Software, Cable Set |
| Classification (IEC 62040-3) | VI-SS-333                |
| UPS technology               | Line Interactive         |

|                                        |                                |
|----------------------------------------|--------------------------------|
| Power class                            | 600 ... 900 VA                 |
| Output (VA/W)                          | 625/375                        |
| Backup time                            | 3 min                          |
| Backup time full/half-load             | 3 / 6 min                      |
| Dimensions (HxWxD)                     | 168 x 105 x 334 mm             |
| Mounting form                          | Turm                           |
| Voltage (input)                        | 230 V                          |
| Voltage (output)                       | 230 V                          |
| Output voltage regulation              | yes                            |
| Frequency                              | 50 Hz                          |
| Connector type (input)                 | cold connector IEC320 C14      |
| Outputs                                | 5                              |
| Connector type (output)                | 2x 3 cold connector IEC320 C13 |
| Phase in/output                        | 230V/230V / 50Hz               |
| Over current protection                | EMI,- RFI-Filter               |
| Max. quantity of delay expansion units | 0                              |
| Delay expansion unit                   | --                             |
| Slots for adapter card                 | 0                              |
| Slot for adapter card                  | --                             |
| Interface                              | USB                            |
| USB 2.0 Interface                      | Yes                            |
| Hot swap batteries                     | No                             |
| Bypass                                 | No                             |
| Additional over current protector      | Telephone/Fax                  |
| Activity                               | Display                        |
| Activity LED                           | --                             |
| Activity Display                       | yes                            |

|                          |         |
|--------------------------|---------|
| incl.Management Software | Windows |
| Internal cooling         | Passive |
| Ambient temperature      | 0-40 °C |
| height                   | 168 mm  |
| width                    | 105 mm  |
| depth                    | 334 mm  |
| Weight                   | 6.4 kg  |

| Backup Time       |         |
|-------------------|---------|
| Capacity (VA / W) | minutes |
| 100               | 50      |
| 200               | 19      |
| 300               | 8       |
| 425               | 5       |
| 525               | 4       |
| 625               | 3       |