Product data sheet
Characteristics

APCRBC143
APC Replacement Battery Cartridge #143



Overview

Model Name	APC Replacement Battery Cartridge #143
Includes	All required connectors , Battery recycling guide , Installation guide , Reusable packaging
Standard Lead Time	Usually in Stock
Product Distribution	Albania , Andorra , Australia , Austria , Belgium , Bosnia And Herzegovina , Bulgaria , Cambodia , Canada , Croatia , Cyprus , Czech Republic , Denmark , Estonia , Finland , France , Germany , Gibraltar , Greece , Hungary , Iceland , Indonesia , Ireland , Italy , Latvia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Malaysia , Malta , Moldova, Republic Of , Myanmar , Nepal , Netherlands , New Zealand , Norway , Philippines , Poland , Portugal , Romania , Russian Federation , Singapore , Slovakia (Slovak Republic) , Slovenia , Spain , Sweden , Switzerland , Thailand , Ukraine , United States , Viet Nam

Output

Battery Output Voltage	120

Batteries & Runtime

Battery Volt-Amp-Hour Capacity	600
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery mounting	Enclosed battery cartridge
Battery mounting	3 - 5
RBC Quantity	1
Battery blocks per string	10

Physical

Net Weight	22.27 kg
Maximum Height	225.0 mm
Maximum Width	279.0 mm
Maximum Depth	481.0 mm
Shipping Weight	25.18 kg
Shipping Width	293.0 mm
Shipping Height	253.0 mm
Shipping Depth	495.0 mm
Units per Pallet	32.0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters

Conformance

Standard warranty	1 year repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains SVHCs