



Advanced Card Systems Ltd.
Card & Reader Technologies

ACR1281U-C2

Card UID Reader



Technical Specifications V1.04



Table of Contents

1.0.	Introduction	3
2.0.	Features	4
3.0.	Typical Applications.....	5
4.0.	Technical Specifications.....	6

List of Figure

Figure 1 : ACR1281U-C2 Sample Application	3
---	---

1.0. Introduction

ACR1281U-C2 is a contactless card UID (Unique Identification Number) reader especially designed to get the UID of any ISO 14443 Parts 1-4 Type A and B-compliant contactless card in an efficient way. Its sole focus is to retrieve the card's UID and display it directly in any text editor such as Notepad, Microsoft® Excel and Microsoft® Word.

When a contactless card (e.g., MIFARE® DESFire® card) is tapped onto the ACR1281U-C2, the reader retrieves the UID and automatically returns the UID to the computer. Since it is HID (Human Interface Device)-compliant, this device does not require any additional driver to be installed in the computer. The ACR1281U-C2 also has an anti-collision feature that ensures only one card is accessed when multiple cards are presented at the same time.

ACR1281U-C2 Card UID Reader can support Windows®, Linux®, Mac OS®, and other embedded systems.




Figure 1: ACR1281U-C2 Sample Application



2.0. Features


- USB 2.0 Full Speed Interface
- USB HID Keyboard Class Emulation
- Smart Card Reader:
 - Contactless Interface:
 - Read/Write speed of up to 848 Kbps
 - Built-in antenna for contactless tag access, with card reading distance of up to 50 mm (depending on tag type)
 - Supports ISO 14443 Part 4 Type A and B cards, and MIFARE® cards
 - Built-in anti-collision feature (only one tag is accessed at any time)
- USB Firmware Upgradability
- Compliant with the following standards:
 - ISO 14443
 - USB HID
 - CE
 - FCC
 - RoHS



3.0. Typical Applications

- e-Government
- e-Banking and e-Payment
- e-Healthcare
- Transportation
- Network Security
- Access Control
- Loyalty Program

4.0. Technical Specifications



Physical Characteristics

Dimensions	120.5 mm (L) × 72.0 mm (W) × 20.4 mm (H)
Weight	140 g
Color	Black

USB Host Interface

Protocol	USB HID Keyboard Class
Connector Type	Standard Type A
Power Source	From USB port
Speed	USB Full Speed (12 Mbps)
Supply Voltage	5 V
Supply Current	Max. 200 mA
Cable Length	2.0 m, Fixed

Contactless Smart Card Interface

Standard	ISO 14443 A and B Parts 1-4
Protocol	ISO 14443 T=CL for ISO 14443-4-compliant cards
.....	T=CL Emulation for MIFARE Classic
Operating Frequency	13.56 MHz
Operating Distance	Up to 50 mm (depending on card type)
Smart Card Read/Write Speed	106 Kbps, 212 Kbps, 424 Kbps, 848 Kbps
Antenna Size	65 mm × 60 mm

Built-in Peripherals

LED	2 single-color: Red and Green
Buzzer	Monotone

Other Feature

Firmware Upgrade	Supported
------------------------	-----------

Operating Conditions

Temperature	0 °C – 60 °C
Humidity	Max. 90% (non-condensing)
MTBF	500,000 hrs

Certifications/Compliance

ISO 14443, USB Full Speed, USB HID, CE, FCC, RoHS



Operating System Support

Windows®, Linux®, Mac OS®



Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.

Mac OS is a trademark of Apple Inc., registered in the U.S. and other countries.

Microsoft, Microsoft Excel, Microsoft Word, and Windows are either registered trademarks or trademarks of the Microsoft Corporation in the United States and/or other countries.

MIFARE and MIFARE DESFire are registered trademarks of NXP B.V. and are used under license.