



Features

- **Studio-quality sound on stage for crystal-clear vocal performance**
- **Same 16 mm low-mass diaphragm found in the critically acclaimed AT2020 side-address studio microphone**
- **Extended frequency response and superior transient response for smooth, natural sonic characteristics**
- **High SPL-handling and wide dynamic range provide unmatched versatility**
- **Cardioid polar pattern reduces pickup of sounds from the sides and rear, improving isolation of desired sound source**
- **Multi-stage grille design offers excellent protection against plosives and sibilance without compromising high-frequency clarity**
- **Rugged all-metal design and construction for years of trouble-free use**
- **Corrosion-resistant contacts from gold-plated XLRM-type connector**
- **Quiet-Flex™ stand clamp provides silent, flexible microphone positioning**

Description

The AT2010 is a handheld condenser microphone with a cardioid polar pattern. It is designed specifically for close-up vocal use in professional live-sound and studio applications.

The microphone requires 48V phantom power for operation.

The cardioid polar pattern of the microphone is more sensitive to sound originating directly in front of the element, making it useful for controlling feedback, reducing pickup of unwanted sounds and providing isolation between performers.

The output of the microphone is a 3-pin XLRM-type connector.

The microphone is enclosed in a rugged housing. Its multi-stage grille design offers excellent protection against plosives and sibilance without compromising high-frequency clarity. The included AT8470 Quiet-Flex™ stand clamp permits mounting on any microphone stand with 5/8"-27 threads. A soft protective pouch is also included.

Operation and Maintenance

The AT2010 requires 48V phantom power for operation.

Output is low impedance (Lo-Z) balanced. The signal appears across Pins 2 and 3; Pin 1 is ground (shield). Output phase is "Pin 2 hot"—positive acoustic pressure produces positive voltage at Pin 2.

To avoid phase cancellation and poor sound, all mic cables must be wired consistently: Pin 1-to-Pin 1, etc.

When using the microphone in settings with a stage monitor speaker, the speaker should be located 180° off axis (at rear of the microphone). This placement, in conjunction with the microphone's uniform cardioid pickup pattern, will virtually eliminate the possibility of undesired audio feedback.

Avoid leaving the microphone in the open sun or in areas where temperatures exceed 110° F (43° C) for long periods of time. Extremely high humidity should also be avoided.

To reduce the environmental impact of a multi-language printed document, product information is available online at www.audio-technica.com in a selection of languages.

Afin de réduire l'impact sur l'environnement de l'impression de plusieurs langues, les informations concernant les produits sont disponibles sur le site www.audio-technica.com dans une large sélection de langue.

Para reducir el impacto al medioambiente, y reducir la producción de documentos en varios leguajes, información de nuestros productos están disponibles en nuestra página del Internet: www.audio-technica.com.

Para reduzir o impacto ecológico de um documento impresso de várias línguas, a Audio-Technica providência as informações dos seus produtos em diversas línguas na www.audio-technica.com.

Per evitare l'impatto ambientale che la stampa di questo documento determinerebbe, le informazioni sui prodotti sono disponibili online in diverse lingue sul sito www.audio-technica.com.

Der Umwelt zuliebe finden Sie die Produktinformationen in deutscher Sprache und weiteren Sprachen auf unserer Homepage: www.audio-technica.com.

Om de gevolgen van een gedrukte meertalige handleiding op het milieu te verkleinen, is productinformatie in verschillende talen "on-line" beschikbaar op: www.audio-technica.com.

本公司基於減少對環境的影響，將不作多語言文件的印刷，有關產品訊息可在 www.audio-technica.com 的官方網頁上選擇所屬語言及瀏覽。

本公司基于减少对环境的影响，将不作多语言文档的印刷，有关产品信息可在 www.audio-technica.com 的官方网页上选择所属语言和浏览。

자원절약, 환경보호를 위해 국문 사용 설명서는 인쇄하지 않았습니다.
제품정보는 www.audio-technica.com 에서 원하는 언어 선택 후에 다운로드 받으실 수 있습니다.

Specifications

Element	Fixed-charge back plate, permanently polarized condenser
Polar pattern	Cardioid
Frequency response	40-20,000 Hz
Open circuit sensitivity	-48 dB (3.9 mV) re 1V at 1 Pa
Impedance	100 ohms
Maximum input sound level	136 dB SPL, 1 kHz at 1% T.H.D.
Dynamic range (typical)	113 dB, 1 kHz at Max SPL
Signal-to-noise ratio ¹	71 dB, 1 kHz at 1 Pa
Phantom power requirements	48V DC, 2 mA typical
Weight	233 g (8.2 oz)
Dimensions	179.1 mm (7.05") long, 50.8 mm (2.00") head diameter
Output connector	Integral 3-pin XLRM-type
Audio-Technica case style	T7
Accessories furnished	AT8470 Quiet-Flex™ stand clamp for 5/8"-27 threaded stands; 5/8"-27 to 3/8"-16 threaded adapter; soft protective pouch

In the interest of standards development, A.T.U.S. offers full details on its test methods to other industry professionals on request.


1 Pascal = 10 dynes/cm² = 10 microbars = 94 dB SPL

¹ Typical, A-weighted, using Audio Precision System One.

Specifications are subject to change without notice.




frequency response: 40–20,000 Hz



LEGEND — 12" or more on axis

polar pattern



Audio-Technica Corporation
audio-technica.com ©2015 Audio-Technica

P#1423-11280B P52573