




REV.	REVISED DESCRIPTION	DATE	CHECKED
A0	FIRST RELEASE	2018/08/09	



① Cable Printing(White):USB 2.0 SHIELDED 28#2C+24#2C
E352563 AWM 20276 80°C 30V VW-1

USB Micro B


CONNECTION



Remark:
1.100% Open/Short Test
2.Conductive Resistance:2ohms MAX
3.Insulation Resistance:5M ohm MIN.
4.The product is Reach/RoHS compliant.

Item NO.	Length(m)
SB0007	3.0m
SB0008	5.0m

⑥	External Mold	Outer Mould 45P PVC, Black	1PC	
⑤	Internal Mold	Inner Mould PE	1PC	
④	Connector	Micro USB Male, Nickle-Plated	1PC	
③	External Mold	Outer Mould 45P PVC, Black	1PC	
②	Connector	USB A Male, Nickle-Plated	1PC	
①	Cable	28+24 USB Cable OD:4.5mm 28+24 (7/0.12BC+HDPE)*1P + (7/0.20BC +PVC)*2C+7/0.12CCS+64/0.12ALB +OD4.5PVC Black		
ITEM	DESCRIPTIONS & SPECIFICATIONS		QTY	REMARK



ACT			
ERP NO.:		SAMPLE DWG NO.:	
DOC No.:		REVISION	A0
CUSTOMER:		UNIT	mm
CUSTOMER P/N:		SCALE	NO
DESCRIPTION		PAGE NO	1/1
APPROVAL		DATE	2018/08/09
CHECKED		DRAWN	