

CS64U / CS64US


4-Port USB KVM Switch

The CS64U/CS64US takes a giant step forward from prior cable KVM models in the Petite series, by offering built-in cables, USB peripheral sharing, and a firmware upgrade function that allows you to keep up with latest available versions.

Furthermore, the CS64U/CS64US features enhanced Video DynaSync[™] technology, which stores the console monitor's EDID (Extended Display Identification Data) to optimize display resolution. The CS64U/CS64US also offers multiplatform support and computer selection via hotkeys to provide the ultimate in desktop convenience.

Setup

PETITE[™]



Features

- One USB console controls four USB computers
- USB mouse port can be used for USB 1.1 hub and USB 1.1 peripheral sharing
- Computer selection via hotkeys
- Select OS via Hotkey
- Audio-enabled
- Multiplatform support – Windows, Linux, Mac and Sun
- Compact design, built-in 1.8m cables (CS64U), 0.9/1.2m cables (CS64US)
- Superior video quality – up to 2048 x 1536; DDC2B
- Video DynaSync[™] – Exclusive ATEN technology eliminates boot-up display problems and optimizes resolution when switching between ports
- Supports multimedia keyboards
- Supports wireless keyboards and mice
- Supports multifunction mice
- Sun/Mac keyboard support and emulation*
- Auto Scan function to monitor computer operation
- Non-Powered
- Firmware upgradable

- * 1. PC keyboard combinations emulate Sun/Mac keyboards
- 2. Sun/Mac keyboards only work with their own computers

Specifications

Function			CS64U	CS64US
Computer Connections			4	
Port Selection			Hotkeys	
Connectors	Console Ports	Keyboard	1 x USB Type A Female (White)	
		Video	1 x HDB-15 Female (Blue)	
		Mouse	1 x USB Type A Female (White)	
		Speaker	1 x Mini Stereo Jack Female (Green)	
	KVM Ports	Keyboard / Mouse	4 x USB Type A Male (White)	
		Video	4 x HDB-15 Male (Blue)	
		Speaker	4 x Mini Stereo Plug Male (Green)	
LEDs	Selected	4 (Green)		
Cable Length		1.8 m	2 x 0.9 m; 2 x 1.2 m	
Emulation	Keyboard / Mouse		USB	
Video		2048 x 1536; DDC2B		
Scan Interval		1-99 secs. (default 5 secs.)		
Environment	Operating Temp.		0-50°C	
	Storage Temp.		-20-60°C	
	Humidity		0 80% RH, Non-condensing	
Physical Properties	Housing		Plastic	
	Weight		0.80 kg	0.77kg
	Dimensions (L x W x H)		10.90 x 9.72 x 2.54 cm	

* The specifications and pictures are subject to change without notice.