



Cat6a S/FTP Bulk Cable, Solid, 23 AWG

LSZH, 305 m Drum (1,000 ft.), CPR-Dca Rated, Gray

Part No.: 705035

EAN-13: 0766623705035 | UPC: 766623705035

The Intellinet Network Solutions Cat6a S/FTP installation cable has a cable construction of 4x2x AWG23/1. The halogen-free cable jacket conforms to IEC 60332-3-24, FRNC-C, LSZH-3 and EuroClass CPR-Dca standards. The cable is best suited for building-structure cabling in secondary and tertiary areas.

Features:

- S/FTP
- CPR-Dca Rated (Construction Products Regulation)
- Standards tested; meets or exceeds current Cat6a standards
- Suitable for building-structure cabling in secondary and tertiary areas
- Recommended for 10/100/1000/10GBase-T, ATM, FDDI, Video, ISDN, Multimedia and PoE applications
- 305 m cable on drum
- Lifetime warranty

Specifications:

Certification and Standards

- IEC61156-5
- ISO/IEC 11801
- CPR-Dca
- RoHS, REACH

Technical Specifications

- Conductor: solid, bare copper
- AWG 23
- Conductor diameter: $1/0.56 \text{ mm} \pm 0.008 \text{ mm}$
- Insulation: FMPE
- Average thickness: 0.40 mm
- Insulation diameter: $1.35 \text{ mm} \pm 0.05 \text{ mm}$
- Aluminum foil on each pair
- Braid: tinned copper
- LSZH jacket
- Rip cord

Performance

- Max. conductor DC resistance 20°C: 93.8 Ohm/km
- Delay skew: $\leq 45 \text{ ns}/100 \text{ m}$
- Pair-to-ground capacitance unbalance: $\leq 330 \text{ pF}/100 \text{ m}$
- Min. insulation resistance: 5000 MOhm/km
- Resistance unbalance: $\leq 4\%$
- Min. bend radius: 8 mm OD

