

Product data sheet

Specifications



NetBotz 125kHz Rack Access Control

NBACS125

Overview

Presentation	Network appliances enabling remote and local access control for your NetShelter SX enclosures.
Lead time	Usually in Stock

Main

Number of rack unit	1U
Communication port protocol	A-Link SNMP
Provided Equipment	Cable ties Door sensor Installation guide Lock handles Proximity Card Proximity reader Rack Mounting brackets User Manual
Product Compatibility	Rack Sensor Pod 150

General

External Sensor Connection Type	Alarm Beacon 1 Modbus Output (RS-485) 1 Relay Output 1
APC Universal Sensors Supported	Door contact Dry Contact Humidity Smoke Fluid Spot Leak Temperature Vibration
Number of Universal Sensor Ports	6
Number of Sensor Pods Supported	6
Sensor Temperature Range	15...50 °C +/- 1 °C 32...122 °F +/- 1.8 °F

Physical

Height	1.73 in (4.4 cm)
Width	17.01 in (43.2 cm)
Depth	2.32 in (5.9 cm)
Net Weight	2.80 lb(US) (1.27 kg)

Mounting preference	No preference
Mounting Mode	Rack-mounted
Environmental	
Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %
Ordering and shipping details	
GTIN	3606481978011
Package weight(Lbs)	5.40 lb(US) (2.45 kg)
Packing Units	
Package 1 Height	7.63 in (19.37 cm)
Package 1 width	35.59 in (90.4 cm)
Package 1 Length	20.83 in (52.9 cm)
Offer Sustainability	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration