



FCS-3402 GEMINI Fixed Dome IP Network Camera, 2-Megapixel, H.265, Vandalproof, 802.3af PoE, Indoor/Outdoor

Product Images



Short Description

- Video compression: H.264, H.265, MJPEG
- Weatherproof IP67-rated housing
- Built-in Micro SDHC/SDXC card slot for local storage
- Supports iPhone/Android phone remote viewing over the Internet

Description

The LevelOne FCS-3402 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 2-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-3402 Should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Additional Information

Number of client	Up to 32 users, 3 levels: Administrator, Operator and User Simultaneous Live View:Up to 6 channels
Data rate	Video Bit Rate: 32 Kbps to 8 Mbps
Frame rate	Main Stream: 50Hz: 25fps (1920 * 1080, 1280 * 960, 1280 * 720) 60Hz: 30fps (1920 * 1080, 1280 * 960, 1280 * 720) Sub-Stream: 50Hz: 25fps (640 * 480, 640 * 360, 320 * 240) 60Hz: 30fps (640 * 480, 640 * 360, 320 * 240)
Management	Saturation, brightness, contrast, sharpness, AGC, White balance adjustable by client software or web browser BLC, 3D DNR
Security	Motion detection, video tampering alarm, illegal login
Video	Region of Interest:1 fixed region for main stream and sub-stream
Power Consumption	12 VDC, 0.4 A, Max: 5 W PoE: (802.3af, 37 V to 57 V), 0.2 A to 0.13 A, Max: 7 W
Approval and compliance	CE/FCC,IP67, IK10
Max. operating temperature (°C)	60
Max. storage temperature (°C)	95
Min. operating temperature (°C)	-30
Supported browsers	Internet Explorer 9.0 or newer (full functionality) Safari with QuickTime installed, and other browsers with VLC installed (partial functionality)
Angle of view (°)	FOV: 8, vertical FOV: 46, diagonal FOV: 102
Button	Reset
Digital zoom	8X
Image sensor	1/2.8" Progressive Scan CMOS
Indicators	Power
IR cut filter	Yes
IR range	Up to 30 meter
Lens	Board LENS 4mm @F2.0
Minimum illumination (lux)	0.01Lux @ (F1.2, AGC ON), 0 Lux with IR

Mount	Ceiling mount
Resolution	50Hz: 25fps (1920 * 1080, 1280 * 960, 1280 * 720) 60Hz: 30fps (1920 * 1080, 1280 * 960, 1280 * 720)
Shutter time	1/3 s to 1/100,000 s
Storage capacity	MicroSDHC /MicroSDXC card slot for local storage
Standards	IEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3af Power over Ethernet (PoE) IEEE 802.1X Network Access Control TCP(IPv6/v4), UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP,FTP,SAMBA UPnP, SNMP, Bonjour
Video format	Main stream: H.265/H.264 Sub-stream: H.265/H.264/MJPEG
Weatherproof rating	IP66
General features	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark
Product weight (kg)	0,5
Product breadth (mm)	111
Product depth (mm)	111
Product height (mm)	82
Color	White
EAN	4015867207697
Model number	FCS-3402
Package contents	FCS-3402 Screw Kit Quick Installation Guide Resource CD (User Manual, Utility, QIG)
Camera Type	Dome
Resistance	Vandalproof, Weatherproof
Zoom Type	Fixed
2-way Audio	Yes
IR Leds for night vision	Yes

