



FCS-5201 GEMINI Fixed IP Camera, 2-MP, H.265

Product Images



Short Description

- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Built-in infrared LEDs for night viewing up to 30m
- Removable IR-cut filter for day and night surveillance
- 2-Megapixel (1920 x 1080) high-definition resolution
- Built-in infrared LEDs for night viewing up to 30m
- Video compression: H.264, H.265, MJPEG
- Supports IPv4/IPv6 network operation

Description

The LevelOne FCS-5201 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 2-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5201 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Additional Information

Number of client	Simultaneous Live View:6 Up to 32 users 3 levels: Administrator, Operator, and User
Data rate	32 Kbps to 8 Mbps
Frame rate	Main Stream: 50Hz: 25fps (1920 * 1080, 1280 * 960, 1280 * 720) 60Hz: 30fps (1920 * 1080, 1280 * 960, 1280 * 720) Sub-stream: 50Hz: 25fps (640 * 480, 640 * 360, 320 * 240) 60Hz: 30fps (640 * 480, 640 * 360, 320 * 240)
Management	Motion detection, video tampering alarm, illegal login
Video	Saturation, brightness, contrast, sharpness, AGC, White balance adjustable by client software or web browser BLC, 3D DNR Region of Interest:1 fixed region for main stream and sub-stream
Power Consumption	12 VDC, 0.4 A, Max: 5 W PoE: (802.3af, 37 V to 57 V), 0.2 A to 0.13 A, Max: 7 W
Approval and compliance	CE/FCC,IP67 TVS 2000V lightning protection, surge protection and voltage transient protection
Max. operating humidity (%)	95
Max. operating temperature (°C)	50
Min. operating temperature (°C)	-30
Supported browsers	IIE7+, Chrome18-42, Firefox5.0+, Safari5.02+
Angle of view (°)	83.6
Button	Reset Button
Digital zoom	8x
Image sensor	1/2.8" progressive scan CMOS
Indicators	Power
IR cut filter	Yes
IR range	Up to 30 meter
Lens	Board lens, Fixed-focal, f=4mm, F2.0
Minimum illumination (lux)	1/3s to 1/100, 000s
Power supply	VDC12V/1A,PoE 802.3af
Resolution	1920 * 1080

Shutter time	1/3 s to 1/100, 000 s, support slow shutter
Standards	IEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3af Power over Ethernet (PoE) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS
Video format	H.264, H.265, MJPEG
Weatherproof rating	IP67
General features	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark
Product weight (kg)	0,28
Product breadth (mm)	69,1
Product depth (mm)	66
Product height (mm)	172,7
Color	White
EAN	4015867207734
Model number	FCS-5201
Package contents	FCS-5201 Quick Installation Guide Resource CD (User Manual, Utility, QIG)
Fast Ethernet RJ45	RJ-45, 10/100 Mbps Ethernet,PoE
Camera Type	Bullet
Resistance	Weatherproof
Zoom Type	Fixed
IR Leds for night vision	Yes

