

Radiator Thermostat

Product ref.: 140280A0



Product features

- Replaces conventional thermostats and controls the radiator according to the individual needs of the user.
- Up to three adjustable week profiles: The room temperature can be adjusted according to individually tailored heating phases (up to 6 per day with configurable temperature)
- The temperature can automatically be reduced during ventilation thanks to the open-window function or in combination with the Homematic IP Window / Door Contact
- Secure installation: Thanks to the metal nut, the device can be securely fixed to all standard radiators
- Easy installation: no need to drain water or to intervene into the heating system
- Manual operation: Temperature changes and activating the boost function (heating up the radiator quickly) can be performed directly on the device
- Comfortable voice control with Amazon Alexa, e.g. via Amazon Echo
- Can be used with the Home Control Access Point in connection with the Homematic IP app, the Homematic Central Control Unit CCU2 as well as with various partner solutions

Technical specifications

Supply voltage	2x 1.5 V LR6/mignon/AA
Current consumption	120 mA (max.)
Battery life	2 years (typ.)
Degree of protection	IP20
Ambient temperature	0 to 50 °C
Dimensions (W x H x D)	58 x 71 x 97 mm
Weight	205 g (incl. battery)
Radio frequency	868.3 MHz/869.525 MHz
Typ. open area RF range	300 m
Connection	M30 x 1.5 mm

Logistical data

Product reference	140280A0
EAN code	4047976402809
Short description	HMIP-eTRV
Packing unit	45
Packing dimensions	122 x 112 x 97 mm

Package contents

Homematic IP Radiator Thermostat

Adapters Danfoss (RA, RAV and RAVL)

Danfoss RAV spigot extension

Support ring

Cylinder head screw M4 x 12 mm and nut M4

1.5 V LR6/mignon/AA batteries (2x)

Operating manual