

Product datasheet

Specifications



Power Cord, C19 to CEE/7 Schuko, 2.5m

AP9875

EAN Code: 0731304189404

Main

Product or component type	Power cord
Input Connection Type	Schuko CEE 7 / EU1-16P
Number of rack unit	0U
Cable length	2.4 m
Number of cables	1

Physical

Colour	Black
Product weight	0.22 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Network frequency	50/60 Hz
permissible voltage	90...250 V
Max line current	16 A
Input current limits	16 A

Output

Max current draw	16 A
Number of power socket outlets	1 IEC 60320 C19
Protection type	Without circuit breaker

Conformance

Product certifications	VDE
------------------------	-----

Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0...15240 m

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	10.2 cm
Package 1 Length	20.3 cm
Package 1 Weight	0.299 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	25.5 cm
Package 2 Width	33.2 cm
Package 2 Length	53.6 cm
Package 2 Weight	4.5 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	10
Package 3 Height	143.99 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	4.5 kg

Logistical informations

Country of origin	CN
-------------------	----

Contractual warranty

Warranty (in months)	24
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	30 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	29 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.4 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
Recyclability potential, in %	30
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins