

Rittal – The System.

Faster – better – everywhere.

Pressure relief stoppers – SZ 2459.500

Date : Feb 10, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Pressure relief stoppers – SZ 2459.500

created: 10.02.2021 on www.rittal.com/com-en



Product description

Description: Especially when enclosures are exposed to changing climatic conditions, pressure differences may cause condensation to form in sealed enclosures. The integral sealing membrane in the pressure relief stopper largely prevents such pressure differences and hence eliminates condensation; additionally, it also prevents the ingress of moisture from the outside. Installed in vertical surfaces to protect against dirt.

Material: Polyamide

Colour: Similar to RAL 9005

Technical specifications: Air permeability up to 120 litres/hour with a pressure difference of 70 mbar
Connection thread M12 x 1.5
For fitting in material thicknesses up to 4 mm

**Protection category
IP to IEC 60 529:** IP 68
IP X8

**Protection category
IP to DIN 40 050-9:** IP 69K

Supply includes: Lock nut

Product description

Packs of: 5 pc(s).

Weight/pack: 0.02 kg

**Copper weight (kg
per piece):** 0

EAN:	4028177516960
Customs tariff number:	39269097
ETIM 7.0:	EC002009
ETIM 6.0:	EC002009
eCI@ss 8.0/8.1:	27180715
eCI@ss 6.0/6.1:	27180715
Product description:	SZ Pressure relief stoppers
Approvals	
Approvals:	UR + C-UR
Certificates:	EAC