



2-Port DVI KVM Switch Kit TK-222DVK (v1.0R)

- Control two computers with one set of console controls
- Designed for use with a DVI-D monitor
- Supports HD resolution above 1080p
- 2 bonus USB share ports for storage devices or printers
- All required cabling included
- No CD installation

The 2-Port DVI KVM Switch Kit, model TK-222DVK, allows you to control two computers with one set of console controls. No driver installation required, simply plug in the included cables to experience beyond HD resolution of 2560 x 1600 pixels. The TK-222DVK supports advanced keyboard and mouse designs and offers two bonus USB share ports to connect storage devices or printers.

Features



Computers

Control up to 2 computers



HD+

Supports resolutions higher than 1080p HD (up to 2560 x 1600 pixels)



2-Way Audio

Full audio support maximizes work station productivity



Console Connectors

Emulation Technology supports most advanced keyboard and mouse designs



DVI-D Monitor

Designed to connect to a monitor's DVI port and supports a 60 Hz refresh rate



Resolution Optimization

Adopts screen resolution from the connected device settings



Computer Ports

Requires free USB and DVI ports from connected computer



Housing

Rugged metal enclosure



USB Share Ports

Two additional USB ports to connect storage drives and printers



Cables Included


All required cables included



Hot Keys

Hot Key command shortcuts

Networking Solution



Console side

PC side

Specifications

Console Port on KVM

- Keyboard: USB
- Mouse: USB
- Monitor: DVI-I
- 2-port USB 2.0 hub
- Speaker jack: 3.5 mm
- Microphone jack: 3.5 mm

Computer Port on KVM (up to 2)

- Keyboard/mouse: USB 2.0 type B
- Monitor: DVI-I
- Speaker jack: 3.5 mm
- Microphone jack: 3.5 mm

Computer Connections (up to 2)

- Keyboard/mouse: USB 2.0 type A
- Monitor: Single Link/ Dual Link DVI-I/DVI-D
- Speaker jack: 3.5 mm
- Microphone jack: 3.5 mm

Monitor Resolution

- Digital: 2560 x 1600 @ 60 Hz
- Analog: 2048 x 1536 @ 60 Hz

Switching Control

- Face panel touch buttons
- Keyboard hot key commands

Switching Notification

- Audio

Scanning Interval

- 10 - 60 seconds (Hot key controls)

Special Features

- Supports Dual Link DVI-D monitor
- Advance mouse and keyboard support
- All time DDC emulation
- Two bonus USB ports
- Metal housing

Operating Temperature

- 0 – 40 °C (32 – 104 °F)

Operating Humidity

- Max 90 % non-condensing

Power

- Input: 100 - 240 V AC, 50/60 Hz, 0.4 A
- Output: 9 V DC, 1 A external power adapter
- Consumption: 0.7 Watts

Dimensions

- 164 x 90 x 45 mm (6.5 x 3.5 x 1.8 in.)

Weight

- 586 g (1.29 lbs.)

Warranty

- 2 year limited

Certifications

- CE
- FCC

Package contents

- TK-222DVK
- Quick Installation Guide
- Power adapter (9 V DC, 1 A)
- 2 sets of DVI-D KVM cables (1.8 m/6 ft.)
- 2 sets of USB 2.0 type A to B cables (1.8 m/6 ft.)
- 2 sets of audio cables (1.8 m/6 ft.)

