

MPN: PROHDMIHDLSSH3

Pro HDMI Cable LSZH 3m

High Performance and High Speed HDMI 2.0 18Gbit Cable with Ethernet.

Supports Resolutions up to 4K@60Hz with HDCP 2.2, CEC and ARC

Ultra flexible.

Low Smoke & Zero Halogen.

- All HDMI resolutions up to 4K (4096x2160p @60Hz), including 3D video
- Support sample rate 4:4:4
- High Dynamic Range (HDR)
- Transfer speed 18 Gbit/s
- HDCP 2.2
- Supports Deep Color, up to 16-bits per channel, including x.v.Color standard
- Supports the 21:9 cinema aspect ratio
- Supports SA-CD, DVD-Audio, DTS-HD Master Audio, Dolby TrueHD, and other high definition audio standards
- Audio Return Channel
- Auto Lip Sync
- Supports up to 32 audio channels and a 1536 kHz audio sampling rate
- Dynamic sound synchronization
- Supports extended CEC (Consumer Electronics Control) commands and functions
- the HDMI Ethernet Channel, and the Audio Return Channel features
- Fully assembled with 19 pins connected
- High quality HDMI A connector, 15um gold min. in contact area for high reliability
- and professional use
- 99,9% pure copper wires for lossless picture transmission
- Triple shielded cable and extra shielding in the connector
- High Flexibility ensuring small bending radius
- Low Smoke & Zero Halogen



Specifications

Features	3D	Yes
	Audio Return Channel (ARC)	Yes
	AWG wire size	28
	Cable jacket material	Low smoke zero halogen (LSZH)
	Cable length	3 m
	Cable material	Copper
	Colour depth	16 bit
	Connector 1	HDMI
	Connector 1 form factor	Straight
	Connector 1 gender	Male

Features	Connector 2	HDMI
	Connector 2 form factor	Straight
	Connector 2 gender	Male
	Connector contacts plating	Gold
	Data transfer rate	18 Gbit/s
	Dolby technologies	DTS-HD Master Audio
	HDCP	Yes
	HDCP version	2.0
	HDMI Ethernet channel	Yes
	HDMI version	2.0
	High Dynamic Range (HDR) supported	Yes
	High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
	High Dynamic Range 10 (HDR10)	Yes
	Maximum refresh rate	60 Hz
	Maximum resolution	4096 x 2160 pixels
	Plug and Play	Yes
	Product colour	Black
	Quantity per pack	1 pc(s)
	RGB support	4:4:4
	RoHS compliance	Yes
	Supported digital audio channels (uncompressed)	32
	Supported graphics resolutions	4096 x 2160
	Supported video modes	2160p
Operational conditions	Operating temperature (T-T)	-20 - 60 °C
Vendor information	Brand Name	Vivolink
	Warranty	99 Year(s)
Weight & dimensions	Cable diameter	7.3 mm

Other products in this series

Cable length	
0.5	PROHDMIHDL SZH0.5
1	PROHDMIHDL SZH1
1.5	PROHDMIHDL SZH1.5
2	PROHDMIHDL SZH2
3	PROHDMIHDL SZH3
5	PROHDMIHDL SZH5
7.5	PROHDMIHDL SZH7.5
10	PROHDMIHDL SZH10
15	PROHDMIHDL SZH15-1 8G
20	PROHDMIHDL SZH20- 18G