

CL100 GEN. 3
SOLID STATE DRIVE

- 2,5" form factor
- SATA III interface
- 3D NAND flash technology
- Capacities up to 960GB
- 3-year warranty limited by the TBW ⁴ parameter and free technical support



PERFORMANCE	120GB	240GB	480GB	960GB
SEQUENTIAL READ PERFORMANCE (MAX) ¹	500 MB/s	520 MB/s	540 MB/s	540 MB/s
SEQUENTIAL WRITE PERFORMANCE (MAX) ¹	360 MB/s	400 MB/s	460MB/s	460 MB/s
TBW ⁴	90 TB	180 TB	350 TB	720 TB

PARAMETERS

CAPACITIES	120GB, 240GB, 480GB, 960GB
DIMENTIONS	100 x 69,85 x 7 [mm]
INTERFACE	SATA III
FORM FACTOR	2,5"
NAND FLASH	3D NAND FLASH
TEMPERATURE	- OPERATIONAL: 0°C ~ 70°C - STORAGE: -45°C ~ 85°C

LOGISTICS DATA

PRODUCT	CAPACITY	P/N	EAN
GOODRAM CL100 SATA III G.3 SSD	120GB	SSDPR-CL100-120-G3	5908267923399
	240GB	SSDPR-CL100-240-G3	5908267923405
	480GB	SSDPR-CL100-480-G3	5908267923412
	960GB	SSDPR-CL100-960-G3	5908267923429

1 Based on tests performed in Crystal Disk Mark 6.0.0 on SSD in FOB (fresh-out-of-box) state . Actual results may vary depending on your system configuration or SSD wear.

2 Based on tests performed in IOMETER on SSD in FOB (fresh-out-of-box) state. Actual results may vary depending on your system configuration or SSD wear.

3 Storage capacity for GOODRAM SSD is provided in decimal values, i.e. 1GB = 1 000 000 000 bytes. Operating systems that use the binary conversion, ie. 1GB = 1,073,741,824 bytes, may show lower storage capacity than provided in this specification. For more information about capacities visit www.goodram.com

4 After exceeding the TBW or 3 years, the SSD is not covered 4 by warranty.

• GOODRAM may make changes to specifications and product descriptions at any time, without notice.

• Product Sheet | GOODRAM CL100 SATA III G.3 SSD | V.2.1 | © 2024 Wilk Elektronik S.A. - GOODRAM