


Open Frame Touch Monitor

HO 325 PTB

31.5" / 80cm Diagonal

LED Backlight – Format 16:9

- 1920 x 1080 Full HD 1080P Resolution
- 10-Point Touch P-Cap Technology
- 178° / 178° Ultra Wide Viewing Angle
- 400 cd/m² High Brightness Panel
- Video Input: HDMI + Display Port
- **IP55 (front) Rating Level**
- **Display Protection: Thickness 3mm**
- **Built-in Speakers**
- ≥7H Toughened Hard Panel Surface
- Slim Profile, Edge-to-Edge True Flat Surface
- Metal chassis, frame and back cover
- VESA Mount and Multiple Mounting Options
- Edge to Edge glass without raised frame
- Orientation: Landscape, Portrait, Face-Up



31.5" / 80 cm

Part. No.: HO 325 PTB

SIZE, RESOLUTION



32"
16:9 Aspect Ratio



Full HD
1920 x 1080

CONNECTIVITY, IP LEVEL



HDMI
DP



IP 55
Water & Dust
Protection

VIEWING ANGLE, VESA



178 Ultra-Wide
Viewing Angle



VESA
Mount

OTHER FEATURES



10 Point Touch




30.000 Hours
Lifetime

HO 325 PTB 32" Open Frame Touch Monitor

Display Size	80 cm / 31.5" Diagonal
Panel Type	TFT – LED Backlight
Aspect Ratio	16:9
Resolution (H x V)	1920 x 1080 Full HD
Brightness (Typ.)	400cd/m ² Panel / 340 cd/m ² Monitor
Contrast (Typ.)	1.200:1 (Typical) / 10.000.000:1 (Active)
Display Area	698,4 x 392,85 mm
Viewing Angle L/R; U/D	178° H / 178° V (CR > 10)
Response Time	8 msec
Pixel Pitch	0,364 (H) x 0,364 (V) mm
Touch Type	Projected Capacitive Type – 10 Point Touch Material Glass + Glass (OGS+CG).
Display Colors	16.7M Colors
Horizontal Frequency	31 ~ 83 kHz
Vertical Frequency	56 ~ 75 Hz
Max Display Frequency	1920 x 1080 @ 60Hz
Input 1	HDMI
Input 2	Display Port
Input 3	USB Type B (Touch)
Speakers	Yes, 2W x 2, Earphone output
Power Consumption	On: 40W; Stand-by: 0.257W; Off: 0.235W
AC Power Range	AC 100 ~ 240 Volt; 50 ~ 60 Hz
Product Dimensions	747 x 64.3 x 451.4 mm (W x D x H)
Packing Dimensions	863 x 163 x 577 mm (W x D x H)
Net / Gross Weight	14,5 Kg / 16,8 Kg

VESA Mounting	100 x 100 mm. VESA Screws: M6, 10mm (Max), pitch 1 Rear Cover Screws: M4, 10mm (Max), pitch 0.7
Display Protection	Thickness 3±0.3 mm
Hardness / Transmittance	≥7H Toughened hard panel surface / ≥86%
IP Rating Level	IP 55 on surface (Front), Dust and Water Protection *
Controls	Menu, Up, Down, Bri (+), Vol (-), Input/Return, Power
LED Backlight life	30.000 hours
Accessory	EU and UK Power cables; HDMI Cable (1.5m); USB Cable for Touch (1,8m); Quick Start Guide, Warranty Card
Certifications	CE, RoHS, EU Energy Label
On Screen Display	15 Languages
Color	Warm, Nature, Cool, User's Mode
Preset Mode	PC, Movie, Game, ECO Modes
Housing	Material: Sheet Metal, Color: Black
Orientation	Landscape, Portrait, Face-Up



Supplier's Name	HANNSpree
Model Name	HO325PTB
Energy Efficiency Class	A
Screen Size (Centimetres)	80.0
Screen Size (Inches)	31.5
On mode power Consumption (W)	40
Annual Energy Consumption* (kWh)	59
Standby-mode Power Consumption (W)	0,26
Off-mode Power Consumption (W)	0,24
Screen Resolution	1920 x 1080

PART. NO.:
HO 325 PTB



4 711404 023002 >

* IP55: The IP Code classifies how resistant a device is to foreign objects and moisture. IP55 means that the monitor is protected from dust and can operate in dusty conditions. It is also protected against water jets projected by a nozzle (6.3mm) from any direction.

HO 325 PTB 32" Open Frame Touch Monitor

