APC Charge Mobile Battery

Technical Specifications Sheet

Designed for Microsoft Surface

Designed in collaboration with

Microsoft Steelcase



Life Is On APC by Schneider Electric

APC Charge Mobile Battery

Technical Specifications



AC Input	
Input Voltage Nominal	100Vac / 120Vac / 230Vac
Input Voltage Range At Full Load	85Vac – 275Vac
Input Current	8A
Input Frequency	50 / 60Hz
DC Output	
Output Watts	200-388 Watts
Output Voltage	24V
AC Output	
Output Voltage	Follow input voltage
Output Current	@120V 3.5A / @230V 1.8A
Output Frequency	Follow input frequency
Connection Ports	
AC Input	IEC 60320 C14
AC Output	IEC 60320 C13
DC Output	Anderson POWERPOLE connection- Female; MSFT connector
Communication	USB Type B
Name Plate	
Name Plate Rating	85-275Vac, 8A, 50-60Hz
Surge Protection	
Surge Energy Rating	190 Joules
Transient Response Time	< 1 ns
Battery Information	
Maximum Charging Time 0% to 100%	<90 Minutes
Battery Runtime	Up to 100 Minutes
Physical	
Battery Type	Lithium-Ion
Ambient Temperature	0ºC to 40ºC // 32ºF to 104ºF
Dimensions (H x W x D)	16.9in (430mm) x 11.0in (280mm) x 3.5 in (90mm) Excluding Mounting Flange
Net Weight	22 lbs. // 11 kg.
Color	Gray
Miscellaneous	
Agency Approvals	CSA/UL 62368-1, UL2054,IEC62133_ed2., UN 38.3
Warranty	3 Years

© 2019 Schneider Electric. All Rights Reserved. Schneider Electric, APC, and Life Is On Schneider Electric are trademarks and the property of Schneider Electric SE, its subsidiaries and affiliated companies. All other trademarks are the property of their respective owners.

Life Is On

APC by Schneider Electric