

Technical Specifications

APC Easy UPS BVX 900VA, 230V, AVR, IEC Sockets | BVX900LI | Downloaded on 09/15/2020 (EST)



APC Easy UPS BVX 900VA, 230V, AVR, IEC Sockets

BVX900LI

Call for More Information 0800 2799254

- Includes: User manual

Output

Output power capacity	480Watts / 900VA
Max Configurable Power (Watts)	480Watts / 900VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60 Hz +/- 1 Hz Sync to mains
Topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Transfer Time	4 ms typical : 6 ms maximum

Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 5 Hz Auto-sensing
Input Connections	IEC 60320 C14
Cord Length	1.2meters
Input voltage range for main operations	140 - 300V
Number of Power Cords	1

Batteries & Runtime

Battery type	Lead-acid battery
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Surge Protection and Filtering

Surge energy rating	273Joules
---------------------	-----------

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Easy UPS BVX 900VA, 230V, AVR, IEC Sockets | BVX900LI | Downloaded on 09/15/2020 (EST)

Physical	
Maximum Height	160MM, 16.0CM
Maximum Width	120MM, 12.0CM
Maximum Depth	355MM, 35.5CM
Net Weight	6.0KG
Shipping weight	6.5KG
Shipping Height	250MM, 25.0CM
Shipping Width	197MM, 19.7CM
Shipping Depth	430MM, 43.0CM
SCC Codes	10731304404498

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 914.4meters
Storage Temperature	-10 - 40 °C
Storage Elevation	0 - 914.4meters

Conformance	
Approvals	CE
Standard warranty	2 years repair or replace

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.