Data sheet

Hot-melt glue applicator

GluePRO 300

Case
EAN 4007841052683



Function description

The new benchmark. The rugged GluePRO 300 with non-slip grip handle is comfortable to hold and has what it takes to become one of your favourite tools. This hot melt glue applicator is the key to convenient, reliable and tireless gluing work without compromising on anything. Practical stroke adjustment makes it possible to set the quantity of glue per stroke for any specific application. Warm-up time is approximately three minutes. Temperature: 190°C. Includes practical case.

Technical specifications

Output, heat-up phase	300 W
Average power consumption	90 W
Temperature	190 – 190 °C
Melt temperature	190 – 190 °C
Temperature accuracy +/-	3 °C
Warm-up time	3 min – 3 min
Delivery rate	25 gr/min
Max. stick diameter	11.7 mm
Function, hanger	Yes
Soft grip	Yes
Stroke adjustment	Yes
Idle mode	No
Dimensions (L x W x H)	283 x 83 x 212 mm
Nozzle can be changed	Yes
Mains power supply	220 – 230 V , 50 / 60 Hz
Model	Case
PU1, net weight	0,580 kg
Manufacturer's Warranty	1 year

Data sheet

Hot-melt glue applicator

GluePRO 300

Case
EAN 4007841052683

Technical specifications

PU1, EAN	4007841052683