

PANTUM

The New Era for Printing

P3300 Series

Monochrome Laser Printer

Reduce your printing cost at utmost

Let the new Pantum P3300 series bring your business value with auto-duplex high speed printing for high working efficiency, low paper jam rate for fluent operation, and eco-friendly separate drum unit and toner cartridge to reduce your cost at utmost. It is ideally suited for users no matter from small business group or from large shared workgroup who require affordable running cost.



**Silent printing mode to lower the noise
and create a comfortable office environment**



**One-Step driver
installation and
direct printing**



**Lowpaper jam rate
design for engine**



Convenient to print



**Office document direct
print from mobile devices**



High print speed



Separate drum and toner



WiFi and print from mobile device available for P3300DW

PANTUM

WWW.PANTUM.COM

KEY SPECIFICATIONS



P3300 Series Monochrome Laser Printer

MODEL

■ P3300DN

■ P3300DW

PRINTING

Print technology	Mono laser	
Print speed	33ppm(A4)/35ppm(Letter)	
First print out time	Less than 8.2 seconds	
Maximum Monthly Duty Cycle	60000 pages	
Recommended monthly volume	750 to 3500 pages	
Processor speed	350 MHz	
Memory	256 MB	
Resolution(dpi)	1200x1200 dpi (Max)	
Printer language	PCL5e, PCL6, PS3, PDF	
Duplex mode	Auto	
Control panel	2Line LCD	
NFC print	No	Yes
Network print	Yes	
Wireless print	No	Yes

PAPER HANDLING

Paper input tray	250 pages
Multipurpose tray	1 pages
Paper output tray	150 pages
Media types	Plain, Thick, Transparency, Cardstock, Lable, Envelope
Media sizes	A4, A5, JISB5, IS0 B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, Monarch Env, DL Env, C5 Env, C6 Env, No.10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2
Media weight	Input tray: 60-105g/ m ² Multipurpose tray: 60-200g/ m ²

GENERAL

Dimensions (WxDxH)	354 x334x 232mm(13.9x 13.1x9.1in)	
Weight (with toner cartridge)	6.8kg (15lb)	
Operating temperature range	10-32 °C (50-95 °F)	
Operating humidity range	20% - 80% RH	
Input voltage	110V Model: AC100-127V(±10%), 50/60Hz(±2Hz), 9A 220V Model: AC220-240V(-15%, +10%), 50/60Hz(±2Hz), 4.5A	
Noise	Printing: ≤52dB(A) Standby: ≤30dB(A)	
Power consumption	Print: Average 525W Standby: 50W Dormant: Less than 2 W	
Operating system compatibility	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.13; Linux (ubuntu12.04/14.04);	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.13; Linux (ubuntu12.04/14.04); iOS 7.0 and above; Android 4.4 and above
Interface	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx Wifi: IEEE 802.11b/g/n

SUPPLIES

Cartridge style	Separate drum and toner	
Starter cartridge capacity ⁽¹⁾	TL-410 (1500 pages)	
Cartridge and drum capacity ⁽¹⁾	Cartridge: TL-410 (1500 pages, Standard); TL-410H (3000 pages, High); TL- 410X (6000 pages , Extra high) Drum: DL-410 (12000pages)	
Starter drum unit lifetime ⁽¹⁾ (Print with A4 paper page by page discontinuously)	DL-410 (12000 pages)	

WHAT'S IN THE BOX

Printer × 1/ 1500 Page Toner Cartridge × 1/ 12000 Page Drum unit × 1/ USB Interface Cable × 1/
Power Cord × 1/ CD-ROM × 1/ Quick Setup Guide × 1

(1) As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)

Copyright © 2019 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.

*Printer data based on Pantum internal testing.