

GC DUAL WH

REFERENCE 02130207 - GC DUAL WH 45 - 8422248078290



DESCRIPTION

- Touch Control Panel with automatic shut-down timer and cleaning filters indicator
- Perimeter suction system
- 3 extraction levels
- Maximum air flow: 1200m3/h
- Minimum sound power: 50dB(A), maximum: 67dB(A)
- BT2 motor. Extra silent. Maximum energy consumption 240W
- Adjustable intensity halogen lighting
- Easy-to-install system
- Dishwasher-washable filters
- Finished in White glass and stainless steel
- Max. Pressure: 455 Pa
- 150/125 mm outlet diameter

FEATURES

EEL class (Energy Efficiency Class)	A
Air flow at minimum speed (m3/h)	340
Air flow at intensive speed (TURBO) (m3/h)	820
Sound Power Level at minimum speed (dB)	50
Sound Power Level at maximum speed (dB)	65
Motor	BT3
Maximum Power Consumption	280
Maximum Pressure	450
Intensive Speed (TURBO) Pressure	470
Control Type	TC3V R
Automatic Switch Off	✓
Electronic Filter Saturation Indicator	✓
Filter Type	Metálico
Anti-grease Filter Number	1
Inner Shield	NO
Extraction Levels	3 + 1
Light Type	EcoLed
Adjustable Intensity Lighting	✓
Nº of Lamps	2
Width (mm)	492
Depth (mm)	253
Outlet Diameter (mm)	150/125
Minimum height distance to a electric worktop hob (mm)	550
Minimum height distance to a gas worktop hob (mm)	650
Installation with Outlet tube to the exterior / Recirculating	AMBAS
Easy Installation System	✓

	02832004
Check Valve	02800904
Noiseless Flexible Duct	02893002
Kit Universal Led	02800000