


PATCHBOX Plus⁺

PATCHBOX Simplify IT

Network with
Confidence

5
YEAR

WARRANTY



PATCHBOX Plus+ Cassettes OS2 / OM4

TECHNICAL SPECIFICATIONS

OS2 CABLE

OS2 RBS 9μ/125μ, G.657.A1, LSZH, Yellow

OM4 CABLE

OM4 RBS 50μ/125μ, LSZH, Erika Violet

CONNECTOR

LC Duplex - LC Duplex / LC Duplex - SC Duplex

CABLE LENGTH

1.7m covers 26RU

CASSETTE PROFILES

Stainless steel, laser-welded

PLASTIC PARTS

Polyoxymethylene POM

OPERATING TEMPERATURE RANGE

+10°C - +45°C

AMBIENT HUMIDITY NON-CONDENSING

10% - 95%

GROSS WEIGHT

0.4kg

PACKAGING DIMENSIONS

69mm x 50mm x 50mm WxDxH

HS-CODE

8544 4210

MADE IN THE EU

ITEMS INCLUDED

1 x PATCHBOX Plus+ OS2 / OM4 Cassette with
LC-LC /LC-SC connector

OS2 VARIANTS

PRODUCT CODE	CONNECTOR TYPE
C60SMAOS211X1Y	LC-LC
C60SMAOS212X1Y	LC-SC

OM4 VARIANTS

PRODUCT CODE	CONNECTOR TYPE
C60MMAOM411X1E	LC-LC
C60MMAOM412X1E	LC-SC


PATCHBOX Plus⁺

PATCHBOX Simplify IT

Network with
Confidence

5
YEAR

WARRANTY



PATCHBOX Plus+ Long Range Cassettes - OS2 / OM4

TECHNICAL SPECIFICATIONS

OS2 CABLE

OS2 RBS 9μ/125μ, G.657.A1, LSZH, Yellow

OM4 CABLE

OM4 RBS 50μ/125μ, LSZH, Erika Violet

CONNECTOR

LC Duplex - LC Duplex / LC Duplex - SC Duplex

CABLE LENGTH

2.7m extractable / 1m over length non-retractable,
covers 48RU from mid-mid

CASSETTE PROFILES

Stainless steel, laser-welded

PLASTIC PARTS

Polyoxymethylene POM

OPERATING TEMPERATURE RANGE

+10°C - +45°C

AMBIENT HUMIDITY NON-CONDENSING

10% - 95%

GROSS WEIGHT

0.42kg

PACKAGING DIMENSIONS

69mm x 50mm x 50mm WxDxH

HS-CODE

8544 4210

MADE IN THE EU

ITEMS INCLUDED

1 x PATCHBOX Plus+ OS2 / OM4 Long Range
Cassette with LC-LC / LC-SC connector

OS2 VARIANTS

PRODUCT CODE	CONNECTOR TYPE
C60SMAOS21131Y	LC-LC
C60SMAOS21231Y	LC-SC

OM4 VARIANTS

PRODUCT CODE	CONNECTOR TYPE
C60MMAOM41131E	LC-LC
C60MMAOM41231E	LC-SC