



Wave Plus

Smart Indoor Air Quality Monitor with Radon Detection



DOWNLOADS



We spend 90% of our time indoors. Measuring our Indoor Air Quality (IAQ) is one of the most important steps we can take in preventing illness and increasing productivity, energy and good health. Airthings, the IAQ specialists and experts in Radon, created the Airthings Wave Plus—the first smart IAQ monitor with Radon detection, designed for homes and all populated spaces. It is the perfect solution for homeowners, employers and facility managers to gain full visibility into six indoor air factors; Radon, carbon dioxide (CO₂), airborne chemicals (TVOCs), humidity, temperature and air pressure. Airthings Wave Plus includes a free app (iOS/Android) and an online dashboard with advanced analytics options.

AIRTHINGS DASHBOARD

Continuous monitoring of your Indoor Air Quality is necessary to minimize potential health effects. The Airthings App and online dashboard provide a quick and easy solution to view, compare and export data for your particular needs. Users have complete access to interpretations of IAQ data and tips to reduce indoor air hazards, optimize ventilation and save energy.

EASY INSTALLATION WITH APP

To install the Wave Plus simply download the Airthings App, pull the battery tab, mount it to the wall or ceiling, and follow the easy instructions in the app to register your device. In addition, simply wave in front of the device to receive a color-coded visual indicator of the overall air quality.

PRODUCT FEATURES

Sensors: Radon, CO₂, TVOC, Temp, Humidity & Air Pressure
Visual indicator: Red/Yellow/Green glow ring
Long battery life:
Bluetooth: 16 months
SmartLink (Hub): 18 months
Future low power mode: TBD months
Supports wall or ceiling mount
Free mobile app for iOS and Android
Web dashboard
Mobile notifications
Wireless connection (Bluetooth or Airthings SmartLink)


ADDITIONAL SPECIFICATIONS

Operational Environment: 4°C to 40°C
Weight: 219g (with batteries)
Dimensions: 12 cm (diameter) x 3.6 cm (height)
Power: 2 AA batteries
Connectivity: Bluetooth & Airthings SmartLink

IAQ SENSOR SPECIFICATIONS

Sensor sampling interval: 5 minutes
Sensor Resolution:
Temperature $\pm 0.1^{\circ}\text{C}$
Humidity $\pm 1\%$
Pressure $\pm 0.15\text{hPa}$
Settling time:
TVOC ~ 7 days
CO₂ ~ 7 days
CO₂ details:
NDIR Sensor (Non-Dispersive Infra-Red)
Measurement range 400–5000 ppm
Non condensing 0 – 85%RH
Optimum Accuracy $\pm 30\text{ppm} \pm 3\%$ within 15 – 35°C
and 0 – 80%RH can be reached after multiple settling cycles on locations with natural indoor CO₂ fluctuations

INTEGRATIONS



RADON SPECIFICATIONS

Radon sampling: Passive diffusion chamber
Detection method: Alpha spectrometry
Measurement range: 0 – 9999 Bq/m³
Accuracy/precision at 200 Bq/m³:
After 7 days $\sim 10\%$ After 2 months $\sim 5\%$

ADDITIONAL INFORMATION

PACKAGE CONTENT

Air Quality Detector
2 AA batteries
Instruction Manual
Mounting screw

PRODUCT CODES

EAN: 7090031109301
SKU: 2910
MODEL: 2930

REQUIREMENTS

iOS 10 or newer / Android 6
or newer, supporting
Bluetooth 4.2 or later

PACKAGE

Weight: 346g
Dimension: 153x153x46mm



RADON



TVOC



CO₂



HUMIDITY



TEMP



PRESSURE